CERTIFICATE OF COMPLIANCE

Certificate Number 20150908-SA6635

Report Reference SA6635-19890807

Issue Date 2015-September-08

 $<\!\!\times\!\!\times\!\!\times\!\!\times\!\!\times\!\!\times$

10027 S 51ST ST, PHOENIX AZ 85044

SECURITRON MAGNALOCK CORP

This is to certify that SPECIAL LOCKING ARRANGEMENTS

representative samples of See Addendum Page

Issued to:

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 294 – Access Control System Units,

ULC-S533-08 - Canadian Standard for Egress Door


Securing and Releasing Devices,


Additional Information: See the UL Online Certifications Directory at

www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.





UL LLC





CERTIFICATE OF COMPLIANCE

 Certificate Number
 20150908-SA6635

 Report Reference
 SA6635-19890807

 Issue Date
 2015-September-08

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.


Models:

USL, CNL: Models EXD-1 and EXD-1F Exit Delay Systems consisting of the following recognized components: BPS-12/24-1, BPS-12, -1, -3, -4.5, -6, -9, -15, BPS-24, -1, -2, 3, -4, -6, -10, BPS-12, -1-CH, -3-CH, -4.5-CH, -6-CH, -9-CH, -15-CH, BPS-24, -1-CH, -2-CH, 3-CH, -4-CH, -6-CH, -10-CH, BPSM-12-6, -9, -15, BPSM-24-4, -6, or -10 Class 2 Output Power Supplies, TSB-3, EL-TSB-3, TSB-3B, EL-TSB-3B, 3700, 3600, 3300, 3100 LMS-1, LML-1, LML-2, TSH-BK, EL-TSH-BK, TSH-CL, EL-TSH-CL, MXD-32 or MXD-62 Exit Devices; XDT Logic Timers; MK or MKN Mortise Keyswitch; Series M32, M62 with suffix C, DV, S, L, LS, F, G, B, D, BD, or R; SAM with suffix C, DV, S, L, LS, F, G, B, D, BD, or R; SAM with suffix C, BD, BD, and/or S; M38, M68 with suffix C, DV, S, L, LS, F, G; M82 with one or more of the required suffixes C, DV, S, L, LS, F, G, B, or BD Locking Devices, and LCP Lock Control Panel. Models may be prefixed with "FA".

Also consisting of the following recognized components: SB-MXD, MXD-32 or MXD-62 Exit Devices. Also consisting of the following recognized components: Dual Sense Bar, Model DSB will be followed by CL, BK, C, or B, may be followed by suffix 42, 48, I, A, IA, or M. Models may be prefix with EL or D.

CNL: Special Lock Arrangement Accessory, Exit Locks: Series M32 with suffix B, D, F, or any combination; M62 and M82 with suffix C, DV, S, L, LS, F, G, B, D, F, G or any combination, or BD; M34R with suffix C, DV, S, L, LS, F, G, B, D, BD, or R; SAM with suffix C, B, D, or BD, and/or S; M38, M68 with suffix C, DV, S, L, LS, D, or T.





UL LLC



