

Experience a safer  
and more open world

## Rockwood 585-24 - 24" Surface Bolt



### Available Finishes:

- US26D/626

#### SIZE:

Bolt Throw: 1 1/4"

Bolt Material: 3/4" x 3/4"

Bolt Length: 24"

#### WEIGHT:

6.1 lbs.

ANSI A156.16:

L04161

## Specifications:

### MATERIAL:

Steel

### FASTENERS:

Bolt: 4 ea. 1/4"-20 x 2 1/4" Flat Head Machine Screws; 4 ea. 1/4"-20 x 1 5/8" Sex Bolts

Strikes: 2 ea. #14 x 2 1/2" Flat Head Sheet Metal Screws, 2 ea. Plastic Anchors;

2 ea. 1/4"-20 x 1" Flat Head Machine Screws, 2 ea. 1/4"-20 Anchors

### FEATURES:

- UL listed for use on inactive leaf of a pair of 3-hour labeled fire doors
- Includes a universal top strike and a mortise bottom strike
- Locks in both the up and down position
- Bolt locks automatically when thrown; can be released only by pressing knob toward door while retracting
- Can be used on any type of door
- Accommodates padlock



### **⚠ WARNING**

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov).