



A WATTS Brand

S19274HDS Swing-Down Halo Eyewash Unit

- Halo™ delivers the most effective eye washdown coverage and spray pattern
- Exceeds American National Standard Z358.1 Specifications
- Durable, ceramic valve
- Precise 20° swing-down activation
- Durable anti-rotational deck-mount unit
- Chrome-plated brass on exposed piping and fittings
- Fully-assembled and factory-tested eyewash or eyewash with hinged dust covers
- Universal identification sign and inspection tag included
- Halo is covered by one or more of the following patents: 9,700,484; 9,314,398; D662220; D673298; D662605; D685920. Other patents pending.

Specifications

Unit design saves space and fits easily into any work environment. Halo eyewash or eye/face wash provides effective wash down coverage and spray pattern. Units operate quickly by pulling swing arm 90° over sink. New vandal resistant ceramic valve limits wear and tear on moving parts, providing dependability and long lasting performance. Safe, steady water flow under varying water supply conditions from 30-90 PSI is assured by integral flow control.



This plumbing fixture is not intended to dispense water for human consumption through drinking or for preparation of food or beverages.

Standard Equipment

Eyewash

The Halo eyewash system offers a high performance rinsing platform that provides rapid relief to an individual's eyes that have been injured by chemicals or particulate. The eyewash includes an integral 5.1 gpm flow control providing water at a safe velocity while maintaining its effectiveness (exceeds minimum water flow of 0.4 gpm at 30 PSI). Safe, steady water flow under varying water supply conditions from 30–90 PSI is assured by integral flow control in the sprayhead assembly.

Valve

Ceramic ½" NPT stay-open valve. The ceramic discs provide a precise 20° activation and deactivation angle, minimizing excessive splashing when the unit is activated.

Pipe and Fittings

Chrome-plated brass.

Water Supply

½" NPT.





Model (select one)	Description
☐ S19274HDS	Deck-Mount Swing-Down Halo Eyewash Unit, Offset
☐ S19-2000	Navigator EFX8 - Emergency Thermostatic Mixing Valve

Tepid Water Options

[Navigator S19-2000 EFX8
Emergency Thermostatic Mixing Valve](#)

[Keltech CLE-Series
Tankless Water Heater](#)

NAVIGATOR



Satisfies ANSI/ISEA Z358.1 tepid water requirements.



A WATTS Brand

S19274HDS Swing-Down Halo Eyewash Unit

Dimensions

(mm)

