

Technical drawing of the 1000mm cable tray assembly, showing top, side, and end views with dimensions and labels.

Top View:

- Labels: OM Length, Extension Length.
- Dimensions: 12.7(±0.2), 45.5(±0.2), 35, 128, 35.
- Section markers: * C, * B, * A, * 128.

Side View:

- Label: For lease.
- Dimensions: 1.5, 35, 96, 1.5.
- Section markers: * F, * E, * D, * 96.

End View (Left):

- Dimensions: 16, 9, 7, 9.5X4.6, Ø6.3, Ø4.4.
- Scale: SCALE 2:1.

End View (Right):

- Dimensions: 14.6, 9, 12.3X4.6, Ø6.3, Ø4.4.
- Scale: SCALE 2:1 On 400mm.

Bottom View (Left):

- Dimensions: 73, 16, 9, 23, 9, 9.5X4.6, 2-Ø6.3, 2-Ø4.4.
- Scale: SCALE 2:1.

Bottom View (Right):

- Dimensions: 9.5X4.6, 2-4.6X9.5, 16, 16, 16, Ø4.6.
- Scale: SCALE 2:1.

E×tension length	Article.No.			Article.No.												
	Zinc plated			Electrophoresis black	OM LENGTH	MM LENGTH	IM LENGTH	A	B	C	D	E	F	Ball Cage/Ball Q'ty	Plastic strape/Ball Q'ty	Packing
	Paired	Cabinet member	Drawer memeber	Paired												
250mm	432.21.970	432.21.550	432.21.560	432.21.370	250	232	245	---	---	---	96	---	---	4"/ 16pcs	126mm/6	1pair/bag,5pairs/ctn
300mm	432.21.971	432.21.551	432.21.561	432.21.371	300	282	295	96	---	---	128	---	---	5"/ 20pcs	155mm/4	1pair/bag,5pairs/ctn
350mm	432.21.972	432.21.552	432.21.562	432.21.372	350	332	345	96	---	---	160	---	---	6"/ 24pcs	181mm/4	1pair/bag,5pairs/ctn
400mm	432.21.983	432.21.583	432.21.563	432.21.984	400	382	395	96	128	---	96	128	---	7"/ 28pcs	207mm/6	1pair/bag,5pairs/ctn
450mm	432.21.974	432.21.554	432.21.564	432.21.374	450	432	445	96	128	---	96	128	72	8"/ 32pcs	233mm/6	1pair/bag,5pairs/ctn
500mm	432.21.975	432.21.555	432.21.565	432.21.375	500	482	495	96	128	64	96	128	96	8"/ 32pcs	233mm/6	1pair/bag,5pairs/ctn
550mm	432.21.976	432.21.556	432.21.566	432.21.376	550	532	545	96	128	96	96	192	64	10" 40pcs	284.5mm/6	1pair/bag,5pairs/ctn
600mm	432.21.977	432.21.557	432.21.567	432.21.377	600	582	595	96	128	128	96	192	96	11" 44pcs	310mm/8	1pair/bag,5pairs/ctn
650mm	432.21.978	432.21.558	432.21.568	432.21.378	650	632	645	96	128	192	96	192	160	12" 48pcs	310mm/8	1pair/bag,5pairs/ctn
700mm	432.21.979	432.21.559	432.21.569	432.21.379	700	682	695	96	128	192	96	192	160	14" 56pcs	310mm/8	1pair/bag,5pairs/ctn

NOTES:
1.LEVER-RELEASE.
2.LOAD CAPACITY 45kg/ 100 lbs.

02			
01	Updated drawing to Baili's version on 2021/01/06	Grace Zhou	Hans Li
Rev.No	Revision Note	Signature	Checked

Acceptable Tolerance in mm DIN ISO 2768-mX								PART NO.: 432.21.XXX		SPECIFICATIONS: 45MM BBR					
>0.5	>6	>30	>120	>400	>1000	>2000	Angle	DRW. NO.: 432.21.XXX		MATL: Cold Rolled Steel					
.6	.30	.120	.400	1.000	2.000	4.000				FINISH: Zinc plated					
±0.1	±0.2	±0.3	±0.5	±0.6	±1.2	±2	±0.5°	DRAWN BY: GZ/NPG		DRW. DATE: 12.12.16					
ISO E								CHECKED BY: GZ/NPG		CHK. DATE: 12.12.16					
THIS DRAWING IS THE PROPERTY OF HAFELE AMERICA COMPANY. IT IS TO BE USED ONLY FOR THE AUTHORIZED AND INTENDED PURPOSE. IT IS TO BE RETURNED UPON REQUEST.								APPROVAL: B/K		APR. DATE:		UNIT:mm		SIZE:A3	