



WayPoint30A

### **Overview**

WayPoint30A Outdoor Power Supply provides 24VAC and/or 28VAC distributed via one or two output(s) for powering CCTV Cameras, heaters and other video accessories.



### **Specifications**

#### **Input:**

- Input: 115VAC, 50/60Hz, 3.5 amp or 230VAC, 50/60Hz, 2.0 amp.

#### **Output:**

- Output options:
  - a. 24VAC @ 12.5 amp max.
  - b. 28VAC @ 10 amp max.
  - c. Both 24VAC and 28VAC not to exceed 10 amp max.
- Output fuses rated @ 15A 32V.

#### **Electrical:**

- Operating Ambient Temperature: -20° C to 50° C.
- 153.55 BTU/Hr.:
- System AC input VA requirement:
  - 115VAC: 402.5VA.
  - 230VAC: 460VA.

#### **Features:**

- Individual power output LEDs.
- Spare fuses included.

#### **Mechanical:**

- NEMA 4/4X, IP66-11 Rated enclosure for outdoor use.
- Lightweight molded fiberglass reinforced polyester enclosure is corrosion resistant and does not contain halogens.
- Lockable stainless steel latches.
- Integral flanges simplify wall or pole mounting.
- Enclosure Dimensions (H x W x D approx.): 13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm).
- Product weight (approx.): 15.45 lbs. (7.01 kg).
- Shipping weight (approx.): 16.75 lbs. (7.6 kg).

### **Agency Approvals**



### **PMK1 Pole Mount Kit (order separately)**

PMK1 pole mount kit is designed to simplify installation of outdoor units.

- Accommodates 2"- 8" (diameter) poles.
- Kit includes:
  - Two (2) powder coated steel mount brackets.
  - Four (4) stainless steel bolts.
  - Four (4) stainless steel lock washers.
  - Two (2) wormgear quick release straps.



**Enclosure Dimensions (H x W x D):**  
 13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm)

