

KEYSWITCHES

CS-400 Series

The CS-400 series Keyswitches are designed as control devices for use with Access Control Systems, Delayed Egress, Electric Dogging and Exit Alarms. Other products that require remote input may also use one of these switches. The 430 and 450 models use momentary switches; the 440 and 460 models use maintained switches.



CS-432, CS-442, CS-452
and CS-462
(2 LEDs - red and green)
Shown with Cylinder
(Cylinder sold separately)



CS-430, CS-440, CS-450
and CS-460
(No LED)
Shown with Cylinder
(Cylinder sold separately)

Benefits

- Available in eight different configurations to meet many different requirements
- Easily fits standard switch outlet box, 1 7/8" deep minimum

Features

- Accepts any standard 5, 6 or 7 pin mortise cylinder with Yale cam
- Heavy duty, extruded stainless steel faceplate
- LED's (green and red) allow 12 or 24 VDC input
- Maintained, momentary switches available
- 2-position switch bracket allows for clockwise and counter-clockwise rotation of cylinder

Technical Information

- Momentary Switch - Form C contacts, 5 amp rating (Switch activated when pushed, deactivated when released)
- Maintained Switch - Form C contacts, 5 amp rating (Switch activated when pushed, deactivated when pushed again)
- 2.75" wide x 4.5" high x 1.75" deep
- When used with a 7 pin cylinder, use collar, Detex p/n 103003

Where Trust is Built™
DETEx®
Life Safety, Security and Security Assurance

Detex Corporation
302 Detex Drive
New Braunfels, Texas 78130-3045 USA
PH. (830) 629-2900
(800) 729-3839
FAX (800) 653-3839
<http://www.detex.com>
USA Sales:
marketing@detex.com
International Sales:
export@detex.com



Cancer & Reproductive Harm - www.detex.com/prop65