

FALCON®

SC70A Series

Heavy duty, Grade 1 door control

Overview

Falcon® SC70A Series heavy duty closers are built for applications that demand reliable door control and easy maintenance. The SC70A Series closers are ANSI Grade 1, ADA compliant and deliver tough performance at an unbeatable value. Choose the SC70A for interior or exterior doors in retail shops, restaurants, apartments, small offices and a variety of other high traffic applications.


Features and benefits:

- Fully adjustable sizes 1-6
- Separate adjustable general speed, latch speed and backcheck
- Common industry hole pattern
- Non-handed for left or right swinging doors
- Double heat-treated pinion
- 1 1/2" diameter, heat-treated forged steel piston
- Listed ANSI/BHMA A156.4, Grade 1
- Meets ANSI A117.1
- Cover is UL approved for use in fire rated assemblies
- UL listed and compliant to UL10C and UBC 7-2 (1997)
- Comes standard with universal screw pack, including self reaming and tapping screws




The right accessories for every job


The non-handed design of the SC70A Series and its quick and easy installation make it perfect for any high traffic application where Grade 1 heavy duty performance is needed.



Regular (RW/PA)




Hold open (HW/PA)




Heavy-duty regular (HD/PA)




Dead stop (DS)




Dead stop hold open (DS/HO)




Spring-n-Stop (SS)




Spring-n-Stop hold open (SS/HO)



Forged arm (FA)




Forged arm with hold open (FA/HO)




Soffit shoe support

Provides anchorage for fifth screw used with soffit shoe where reveal is less than 3 1/16" (78mm).




Blade stop spacer

Required to lower parallel arm shoe to clear 1/2" (13mm) blade stop.




Auxiliary shoe

Requires a top rail of 7" (178mm). Optional shoe replaces PA shoe for parallel arm mounting of regular arm with overhead holder/stop.




Plate

Required for hinge side mount where top rail is less than 3 7/8" (98mm). Required for top jamb mounting where head frame is less than 3 7/8" (98mm).



Parallel arm plate

Required for parallel arm mounting where top rail is less than 6" (152 mm), measured from the stop. Plate requires 1 3/4" (44mm) minimum top rail measured from stop.



Cover

Standard, non-handed, full plastic cover encloses the closer body.

Available finishes



622
Matte black



689
Aluminum



695
Dark bronze



696
Brass

About Allegion

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries. For more, visit www.allegion.com.