


Accessories

Transformers

For electric strikes, bells, buzzers, chimes, and other low voltage devices. A complete line of U.L. Listed step down transformers. Easy to install, low voltage, 120AC primary for residential, commercial and industrial uses. Transformers will safely take themselves off line when they overheat. Transformers can be either base mounted or attached to standard knockouts on boxes or cabinets (except plug-in types.) All primary leads are pre-stripped for quick connection.

(1)




522 – (1) – LOCKNUT TYPE (AC)

- For standard 1/2" knockouts
- 120 volt primary AC
- 2-5/32"D x 2-1/2"H x 2"W 8oz
- Electric Characteristics: **16VAC – 10VA – 0.625 AMPS**



525 – (2) – CLAMP ON TYPE/TRI VOLT (AC)

- Equipped with convenient screw-bracket mounting clamp for standard 1/2" knockouts
- 120 volt primary AC
- 2-1/4"D x 2-3/16"H x 2-5/16"W 13oz
- Electric Characteristics: **8VAC – 10VA – 1.25 AMPS**
- 16VAC – 10VA – 0.62 AMPS**
- 24VAC – 20VA – 0.83 AMPS**



(2)

598 – (2) – CLAMP ON TYPE/TRI VOLT (AC)

- Equipped with convenient screw-bracket mounting clamp for standard 1/2" knockouts
- 120 volt primary AC
- 2-15/16"D x 2-7/32"H x 2-11/32"W 1lb 6oz
- Electric Characteristics: **8VAC – 20VA – 2.50 AMPS**
- 16VAC – 30VA – 1.88 AMPS**
- 24VAC – 30VA – 1.25 AMPS**

(3)



599 – (2) – CLAMP ON TYPE (AC)

- Equipped with convenient screw-bracket mounting clamp for standard 1/2" knockouts
- 120 volt primary AC
- 2-15/16"D x 2-3/16"H x 2-11/32"W 1lb 6oz
- Electric Characteristics: **24VAC – 40VA – 1.65 AMPS**



(4)



5201 – (3) – PLUG IN TYPE (AC)

- 120 volt primary AC
- 2"D x 3"H x 2-1/2"W 7oz
- Electric Characteristics: **24VAC – 20VA – 0.834 AMPS**

5203 – (3) – PLUG IN TYPE (AC)

- 120 volt primary AC
- 2"D x 3"H x 2-1/2"W 7oz
- Electric Characteristics: **16VAC – 20VA – 1.250 AMPS**

5204 – (3) – PLUG IN TYPE (AC)

- 120 volt primary AC
- 2"D x 3"H x 2-1/2"W 7oz
- Electric Characteristics: **12VAC – 20VA – 1.667 AMPS**

5205 – (4) – PLUG IN TYPE/TRI VOLT (AC)

- 120 volt primary AC
- 2"D x 3"H x 2-1/2"W 7oz
- Electric Characteristics: **8VAC – 10VA – 1.25 AMPS**
- 16VAC – 10VA – 0.62 AMPS**
- 24VAC – 20VA – 0.83 AMPS**

(5)




5208 – (5) – PLUG IN TYPE (DC)

- 120 volt primary AC, Corded output lead
- 2"D x 3-1/4"H x 2-3/8"W 1lb 2oz
- Electric Characteristics: **12VDC – 12VA – 1.00 AMPS**

5209 – (5) – PLUG IN TYPE (DC)

- 120 volt primary AC, Corded output lead
- 2"D x 3-1/4"H x 2-3/8"W 1lb 2oz
- Electric Characteristics: **24VDC – 12VA – 0.50 AMPS**

(6)



SR1 – (6) – SILICON RECTIFIER (SR-1) **Not Recommended for 4850**

- For converting AC voltage to DC voltage
- For AC power supplies up to 27 volt AC 1 amp.
- Note: DC strikes do not buzz, click only
- Size 1" x 1/2" x 1"
- Electric Characteristics: **12-27VAC – 1.00 AMPS**