

## cylindrical locksets

### 5400LN series cylindrical lever locksets

Designed for industrial, commercial and institutional use, the Yale 5400LN offers no compromise when it comes to reliability and performance. With construction features such as our Free Wheeling lever mechanism, wear-resistant chassis plates, heavy-duty return springs and patented (Patent No. 6,131,970) door thickness adjustment, it's easy to see why it's a favorite among those who demand the highest standard of product quality. See pages 33-34 for electrified information.




All 5400LN functions feature the Free Wheeling lever mechanism. When the outside lever is locked, it will rotate freely up and down while remaining securely locked.



### features




















<b>ANSI/BHMA:</b>	A156.2, Series 4000 Grade 1	<b>BHMA</b> CERTIFIED
<b>UL-cUL:</b>	UL-cUL fire-rated up to 3 hours	
<b>Windstorm:</b>	Certified (refer to local codes)	Hurricane
<b>Mechanism:</b>	Heavy-gauge steel, zinc-plated, dichromated	
<b>Backset:</b>	2-3/4" standard; 3-3/4" or 5" extension link available to order	
<b>Latchbolt:</b>	1/2" stainless steel throw standard; 3/4" throw available to order	
<b>Guardbolt:</b>	Deadlocks latchbolt when door is closed; standard on all locking functions	
<b>Door Thickness:</b>	Adjustable from 1-3/4" to 2". Available to 2-1/4" doors to order.	
<b>Fronts:</b>	2-1/4" x 1-1/8" beveled standard; flat fronts available to order	
<b>Lead Shielding:</b>	Available to order	
<b>Cylinders:</b>	Brass, 6-pin, keyed-random cylinder with two keys furnished standard, 7-pin available to order. For other cylinder and keying options, see page 29.	
<b>Reversibility:</b>	Non-handed	
<b>Strikes:</b>	1-1/4" curved lip for 1-3/4" door standard; other lip lengths available to order; all reversible	
<b>Finishes:</b>	Available in 13 finishes	
<b>Warranty:</b>	7-year mechanical	

### 5400LN series trim

			
<b>Augusta AU</b>	<b>Monroe MO</b>	<b>Pacific Beach PB</b>	

Levers available to accept small format interchangeable cores and large format interchangeable cores from ASSA®, Medeco® and Schlage®. Fixed core cylinders available with keyways from Corbin®, Corbin Russwin®, Russwin®, Sargent® and Schlage®.

## lockset functions

Function/ Application	(ANSI) Model Nos.	Mortise Locksets	(ANSI) Model Nos.	Cylindrical Knob Locksets	(ANSI) Model Nos.	Cylindrical Lever Locksets/ Monolocks
Passage or Closet Latch	<b>(F01)</b> <b>Knob</b> 8801 <b>Levers</b> 8801FL SL8801FL 8801RL		<b>(F75)</b> 5401 4701 4601		<b>(F75)</b> 5401LN 5301LN 4701LN 4601LN 4301LN 6401LN	
Privacy, Bedroom or Bath Lock	<b>(F19)</b> <b>Knob</b> 8802 <b>Levers</b> 8802FL SL8802FL 8802RL		<b>(F76A&amp;B)</b> 5402 4702 4602		<b>(F76A&amp;B)</b> 5402LN 5302LN 4702LN 4602LN 4302LN 6402LN	
Patio or Privacy Lock	N/A	N/A	N/A	N/A	<b>(F77)</b> 5403LN 5303LN 4703LN 6403LN	
Entry Lock	N/A	N/A	N/A	N/A	<b>(F82A&amp;B)</b> 5404LN 5304LN 4704LN 4604LN 6404LN	
Storeroom or Closet Lock	<b>(F07)</b> <b>Knob</b> 8805 <b>Levers</b> 8805FL SL8805FL 8805RL		<b>(F86)</b> 5405 4705 4605		<b>(F86)</b> 5405LN 5305LN 4705LN 4605LN 4305LN 6405LN	
Service Station Lock	N/A	N/A	<b>(F92)</b> 5406		<b>(F92)</b> 5406LN 5306LN 4706LN 6406LN	
Entry Lock	<b>(F04)</b> <b>Knob</b> 8807 <b>Levers</b> 8807FL SL8807FL 8807RL		<b>(F109)</b> 5407 4707 4607		<b>(F109)</b> 5407LN 5307LN 4707LN 4607LN 4307LN 6407LN	
Classroom Lock	<b>(F05)</b> <b>Knob</b> 8808 <b>Levers</b> 8808FL SL8808FL 8808RL		<b>(F84)</b> 5408 4708 4608		<b>(F84)</b> 5408LN 5308LN 4708LN 4608LN 4308LN 6408LN	
Note: Shaded area denotes rigid lever or knob.		Note: Shaded area denotes rigid knob.		Note: Shaded area denotes Free Wheeling lever (except 4300LN and 4600LN).		