

Heavy-duty overhead door holder and stop for exterior, vestibule or interior doors, either single or double acting

**Now available
US32D & US32**

**1000 SERIES
CONCEALED**



WHEN ORDERING, please list:

Model number

Door closer number or other hardware

Mounting means of the door and butt size

Hold-open or dead-stop degree

Door opening and thickness

Finish

STANDARD FEATURES

- For All Stainless Steel Components - Prefix N
- Non-handed/reversible
- Single point hold-open in increments of 5° from 85° to 110°
- Hold-open knob can be disengaged to act as a stop only
- 5° to 7° shock compression following hold-open point
- Steel shock absorbing spring
- Die cast end block and shock block
- Maximum opening 110°, minimum door thickness 1 3/4"
- Both wood and machine screws included
- Available in all BHMA plated and sprayed finishes

**All Stops
Warnock Hersey
listed**

SPECIFICATIONS:

Stop only function to be Warnock Hersey listed as manufactured by ABH.

*Material:
steel or stainless steel channel 3/32" thick and 1 1/8" depth;
arm 1/4" thick and 1" wide;
jamb bracket 1/4" thick and 1" wide;
sliding block shall have easy access for tension adjustment.*

STAINLESS STEEL SPECIFICATIONS:

All parts stainless steel as manufactured by ABH

DOOR FRAME OPENING		HOLDER NUMBER		
BUTTS OFFSET PIVOTS	CENTER HUNG	HOLD-OPEN	STOP	FRICTION
27" - 29 15/16"	30" - 32 15/16"	1011	1021	1031
30" - 35 15/16"	33" - 38 15/16"	1012	1022	1032
36" - 39 15/16"	39" - 42 15/16"	1013	1023	1033
40" - 43 15/16"	43" - 46 15/16"	1014	1024	1034
44" + Greater	47" + Greater	1015	1025	1035
BHMA NUMBER		C01511	C01541	C01531
FED. SPEC TYPE		1160	—	

Contact ABH for special templating or other door opening
Average weight/unit 6 lbs.

www.abhmfg.com
E-mail: abhinfo@abhmfg.com
Architectural Builders Hardware Mfg., Inc.
 1222 Ardmore Ave., Itasca, IL 60143
630.875.9900; FAX 800.9FAXABH (932.9224)

© 2005 ABH Mfg., Inc.
Printed in USA 02/05

