



MAGNUM

PREMIUM LUBRICANT WITH PTFE



FEATURES

- Excellent for heavy load applications
- PTFE additives improve performance
- Extends equipment life
- Displaces moisture
- Protects against rust and corrosion
- Does not contain chlorinated solvents
- Safe to use on most surfaces
- NSF[®] H2 registered #128980 (aerosol); #128981 (bulk)
- Flash point of 175°F (79°C)
- Inverta Spray Valve



Nonfood Compounds Program Listed
Category Code: H2 Registration
#128980 (aerosol); #128981 (bulk)

PACKAGES

Net Fill

- 11 oz. (312 grams) aerosol
- 5 gal. (18.93 liters)

Part No.

- 00616
- 00605

APPLICATIONS

- Bearings and Valves
- Cables and Linkages
- Dies, Bits and Fasteners
- Engines and Electric Motors
- Hoists, Lifts and Draglines
- Metal Parts and Hand Tools
- Parts in Storage
- Production and Transportation Equipment
- Pulleys and Rollers
- Slides and Tracks

PROPERTIES

Appearance/Physical State:

Brown

Boiling Point:

383°F (195°C)

Evaporation Rate:

<0.1 (Butyl Acetate=1)

HMIS:

1, 2, 0

Specific Gravity (water=1):

0.85 – 0.87 @ 20°C

Flash Point (TCC):

175°F (79°C)

Vapor Pressure:

630 kPa (25°C)

Viscosity:

<7 centistokes @ 25°C

VOC Content:

3.0%, 0.2 lbs/gal., 26 g/L (bulk)

2.9%, 0.2 lbs/gal., 25 g/L (aerosol)



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2012 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2095 • Rev. 5/2012