



engineered with you in mind

Part No.: 725901

Applications:

This document establishes the specifications for a composite cable individually and overall jacketed used for communication applications.

Component 1 Construction Details:

Number of Conductors: 4/C
Conductor: 18AWG Stranded Bare Copper.
Insulation Material: Remguard Plenum Polymer
Insulation Color Code: Black, Red, White, Green
Jacket Material: Remguard Plenum Polymer
Jacket Color: Gray
Rip Cord: Nylon
Nominal Diameter: 0.179 in.
Surface Print: 3122598 POWER LOCK CMP 4/18AWG C(ETL)US
A B C D E 0 1 2 3 4 5 6 7 8 9

Component 2 Construction Details:

Number of Conductors: 6/C (3 Pairs)
Conductor: 22AWG Stranded Bare Copper.
Insulation Material: Remguard Plenum Polymer
Insulation Color Code: Black paired with Red
White paired with Green
Orange paired with Brown
Overall Shield: Aluminum/Polyester
Drain Wire: Stranded Tin Copper
Jacket Material: Remguard Plenum Polymer
Jacket Color: Orange
Rip Cord: Nylon
Nominal Diameter: 0.200 in.
Surface Print: 3122598 CARD READER CMP 3P/22AWG C(ETL)US
A B C D E 0 1 2 3 4 5 6 7 8 9

Component 3 Construction Details:

Number of Conductors: 2/C
Conductor: 22AWG Stranded Bare Copper.
Insulation Material: Remguard Plenum Polymer
Insulation Color Code: Black, Red
Jacket Material: Remguard Plenum Polymer
Jacket Color: White
Rip Cord: Nylon
Nominal Diameter: 0.122 in.
Surface Print: 3122598 DOOR CONTACT CMP 2/22AWG C(ETL)US
A B C D E 0 1 2 3 4 5 6 7 8 9

Customer Approval: _____

Date: _____

Issue Date: 05/11
Revision: 4

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

PO Box 488 468 RT17A Florida, NY 10921

Customer Service: 800-431-3864

Fax: 845-651-4160

Website: www.remee.com

Access Control Cable Plenum

ETL listed for guaranteed performance
Made in the USA

Component 4

Construction Details:

Number of Conductors: 4/C
Conductor: 22AWG Stranded Bare Copper.
Insulation Material: Remguard Plenum Polymer
Insulation Color Code: Black, Red, Green, White
Jacket Material: Remguard Plenum Polymer
Jacket Color: Blue
Rip Cord: Nylon
Nominal Diameter: 0.140 in.
Surface Print: 3122598 REX/SPARE CMP 4/22AWG
C(ETL)US A B C D E 0 1 2 3 4 5 6 7 8 9

Overall Construction Details:

Construction: Four components are cabled together and overall jacketed
Jacket Material: Remguard Plenum Polymer
Nominal Jacket Thickness: 0.015 in.
Nominal Diameter: 0.410 in.
Surface Print: 3122598 ACCESS CONTROL CABLE
CMP 4/18AWG 12/22AWG C(ETL)US +
Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms.

Technical Details:

Temperature Rating	
Operation:	-20°C to 60°C
Nominal Weight:	99 lbs. / 1,000 feet

Codes & Listings:

- NEC Article 800
- UL Subject 444, Type CMP
- C(ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



MADE IN THE USA



It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.