### Heavy-duty overhead door holder and stop for exterior, vestibule or interior doors, single acting



# 9000 SERIES SURFACE MOUNTED



#### STANDARD FEATURES

- **■** For all Stainless Steel Components Prefix N
- Non-handed/reversible
- Single point hold-open in increments of 5° from 85° to 110°
- Hold-open knob can be disengaged to act as a stop only
- 5° to 7° shock compression following hold-open point
- Steel shock absorbing spring
- Die cast end block and shock block
- Maximum opening 110°, minimum door thickness 1 3/4"
- Wood, machine screws and sex bolts included
- Available in all BHMA plated and sprayed finishes

SPECIFY ANGLE JAMB BRACKET 90541 FOR HINGE SIDE OR FLUSH TRANSOM MOUNTING

DOOR FRAME OPENING		HOLDER NUMBER		
BUTTS OFFSET PIVOTS	CENTER HUNG	HOLD- OPEN	STOP	FRICTION
28" - 29 15/16"	30" - 33 15/16"	9011	9021	9031
30" - 31 15/16"	34" - 35 15/16"	9012	9022	9032
32" - 35 15/16"	36" - 38 15/16"	9013	9023	9033
36" - 39 15/16"	39" - 40 15/16"	9014	9024	9034
40" - 41 15/16"	41" - 44 15/16"	9015	9025	9035
42" - 43 15/16"	45" - 46 15/16"	9016	9026	9036
44" + Greater	47" + Greater	9017	9027	9037
BHMA NUMBER		C02511	C02541	C02531
FED. SPEC TYPE		1161	1161A	_

Contact ABH for special templating or other door opening Average weight/unit 6 lbs.

## WHEN ORDERING, please list:

Model number

Door closer number or other hardware

Mounting means of the door and butt size

Hold-open or dead-stop degree

Door opening and thickness

**Finish** 

### **SPECIFICATIONS:**

Stop only function to be Warnock Hersey listed as manufactured by ABH.

#### Material:

bronze/steel/stainless steel; channel 3/32" thick and 1 1/8" depth; arm 1/4" thick and 1" wide; jamb bracket 1/4" thick and 1" wide; sliding block shall have easy access for tension adjustment.

### STAINLESS STEEL SPECIFICATIONS:

All parts stainless steel as manufactured by ABH.



**Architectural Builders Hardware Mfg., Inc.** 1222 Ardmore Ave., Itasca, IL 60143 **630.875.9900; FAX 800.9FAXABH** (932.9224)



