

Catalog Number 01415

**UPC Number** 60198601415

**Description** Nylon Fully Insulated Male Disconnect 22-16



#### **Features**

- Nylon Color Coded insulation on barrel and disconnect tab
- Manufactured from high strength copper alloy
- Electro-tin plated for corrosion resistance
- Easy entry expanded insulation eliminates strand "Hang Up", increases the crimping rates and the reliability of the wire
- Wire range stamped on the surface for easy interpretation
- Brazed seams prevent splitting under maximum pressure
- Serrated barrel & flared position of sleeves provide excellent contact & mechanical stress relief at insulation & barrel junction
- Packed in Zip Lock plastic bags with punched hole for pegboard hanging

i	f F	
Ļ	B	
	Ĭ	C D

## General

Insulation Type Nylon Material Brass

Finish Electro-Tin Plated

Color Red
Wire Range 22-16
Tab Size .032 X .250

#### **Dimension Information**

Stock Thickness	0.016
L Inches (mm)	0.906
B Inches (mm)	0.433
C Inches (mm)	0.067
D Inches (mm)	0.157
F Inches (mm	0.303
W Inches (mm	0.25

#### **Specifications**

Temperature Rating 105°C
Voltage Rating 300 V
Flammability Rating UL94V-O
Amp Rating 10 Amps

### **Packaging**

Bag Qty 25 Master Bag Qty 100

# Certifications

UL Yes cUL Yes RoHS Yes

