# MORRIS CAT#: 10412B
# Nylon Fully Insulated Disconnects
# Female - 16-14 Wire, .250x.032
# Tab Bulk Bag




**Features:**

Nylon Fully Insulated Disconnects Female - 16-14 Wire, .250x.032 Tab features include:

- Fully Insulated Female Disconnects feature Nylon Insulation
- Color Coded insulation for easy identification
- Manufactured from High Strength Brass
- Electro-Tin Plated for corrosion resistance
- Easy Entry Expanded Insulation eliminates strand “Hang Up”, increasing crimping rates and provides mechanical strain relief
- Wire range stamped on the surface for easy interpretation
- Terminal Barrel has Butted Seam
- Serrated Barrel provides excellent electrical contact & resistance to pull-out forces
- 221°F (105°C) 600 Volts Max
- Maximum Electric Current: 22 AWG - 3 Amp, 20 AWG - 4 Amp, 18 AWG - 7 Amp, 16 AWG - 10 Amp, 14 AWG - 15 Amp, 12 AWG - 20 Amp, 10 AWG - 24 Amp
- cULus Listed
- Dimension Measurements = Inches
- Order Qty of 1000 = 1 Bag of 1000

| AWG | 22 | 20 | 18 | 16 | 14 | 12 | 10 |
|---|---|---|---|---|---|---|---|
| AMP | 3 | 4 | 7 | 10 | 15 | 20 | 24 |

**MAXIMUM ELECTRIC RATING:** 221°F (105°C) 300 Volts
**INSULATION MATERIAL:** Nylon
**TERMINAL MATERIAL:** Electro-Tin Plated Brass
**FEATURES:** Serrated Barrel, Expanded Insulation, Rectangular Housing Shape




DIMENSIONS = INCHES

| CAT NO. | TYPE | COLOR | WIRE SIZE | TAB SIZE | W | F | L | B | C | D | T | BAG QTY | MASTER BAG QTY |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 10412B | FEMALE | BLUE | 16-14 | .250 X .032 | .260 | .295 | .866 | .433 | .091 | .177 | .032 | 1,000 | 10,000 |