MORRIS CAT#: 10416B
Nylon Fully Insulated Disconnects
Male - 16-14 Wire, .250x.032 Tab
Bulk Bag




Features:

Nylon Fully Insulated Disconnects Male - 16-14 Wire, .250x.032 Tab features include:

- Fully Insulated Male Disconnects feature Nylon Insulation
- Color Coded insulation for easy identification
- Manufactured from High Strength Brass
- Electro-Tin Plated for corrosion resistance
- Easy Entry Expanded Insulation eliminates strand “Hang Up”, increasing crimping rates and provides mechanical strain relief
- Wire range stamped on the surface for easy interpretation
- Terminal Barrel has Butted Seam
- Serrated Barrel provides excellent electrical contact & resistance to pull-out forces
- 221°F (105°C) 600 Volts Max
- Maximum Electric Current: 22 AWG - 3 Amp, 20 AWG - 4 Amp, 18 AWG - 7 Amp, 16 AWG - 10 Amp, 14 AWG - 15 Amp, 12 AWG - 20 Amp, 10 AWG - 24 Amp
- cULus Listed
- Dimension Measurements = Inches
- Order Qty of 500 = 1 Bag of 500

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221ºF (105ºC) 300 Volts
INSULATION MATERIAL: Nylon
TERMINAL MATERIAL: Electro-Tin Plated Brass
FEATURES: Serrated Barrel, Expanded Insulation, Rectangular Housing Shape



DIMENSIONS = INCHES

CAT NO.	TYPE	COLOR	WIRE SIZE	TAB SIZE	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
10416B	MALE	BLUE	16-14	.250 X .032	.250	.303	.945	.433	.091	.177	.032	500	5,000