



MORRIS CAT#: 11130-11133
Non-Insulated Ring Terminals - Large AWG




AWG	8	6	4	2
AMP	70	95	125	170

MAXIMUM ELECTRIC RATING: 302°F (150°C) 600V

TERMINAL MATERIAL:

Electro-Tin Plated Copper - Brazed Seam

FEATURES: Serrated Barrel



Features:

Non-Insulated Ring Terminals features include:

- Non-Insulated Ring Terminal Material: High Strength Electro-Tin Plated Copper
- Brazed Seam
- Serrated Barrel with Brazed Seam provides Excellent Electrical Contact & resistance to pull-out forces
- Maximum Electrical Current: 22 AWG - 9 Amp, 20 AWG - 12 Amp, 18 AWG - 17 Amp, 16 AWG - 18 Amp, 14 AWG - 30 Amp, 12 AWG - 35 Amp, 10 AWG - 50 Amp, 8 AWG - 70 Amp, 6 AWG - 95 Amp, 4 AWG - 125 Amp, 2 AWG - 170 Amp
- 302°F(150°C) 600 Volts Max
- cULus Listed
- Dimension Measurements = Inches
- Order Qty of 100 = 1 Bag of 100

DIMENSIONS = INCHES

CAT. NO.	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY
11131	2	5/8	.669	1.181	.917	2.047	.551	.524	.370	.071	100
11132	2	11/16	.748	1.181	.917	2.047	.551	.524	.370	.071	100
11133	2	3/4	.827	1.181	.917	2.047	.551	.524	.370	.071	100