




MORRIS CAT#: 11934B
Nylon Insulated Double Crimp Female
Disconnects - 12-10 Wire, .032x.250 Tab



Features:

Nylon Insulated Double Crimp Female Disconnects - 12-10 Wire, .032x.250 Tab features include:

- Female Double Crimp Disconnects feature Nylon Insulation
- Color Coded insulation for easy identification
- Manufactured from High Strength Brass
- Electro-Tin Plated for corrosion resistance
- Easy Entry Expanded Insulation eliminates strand “Hang Up”, increasing crimping rates and provides mechanical strain relief
- Wire range and tab size stamped on the surface for easy interpretation
- Terminal Barrel has Butted Seam
- Serrated Barrel provides excellent electrical contact & resistance to pull-out forces
- Double Crimp Extended Crimp Sleeve provides for multiple crimps resulting in improved electrical contact and pull-out force resistance
- 221°F (105°C) 600 Volts Max
- Maximum Electric Current: 22 AWG - 3 Amp, 20 AWG - 4 Amp, 18 AWG - 7 Amp, 16 AWG - 10 Amp, 14 AWG - 15 Amp, 12 AWG - 20 Amp, 10 AWG - 24 Amp
- cULus Listed
- Dimension Measurements = Inches
- Order Qty of 500 = 1 Bulk Bag of 500



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts
INSULATION MATERIAL: Nylon
TERMINAL MATERIAL: Electro-Tin Plated Brass
DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps
FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
11934B	YELLOW	12-10	.032 X.250	.260	.295	.925	.512	.134	.256	.016	500	10,000