MORRIS CAT#: 11976B
Nylon Fully Insulated Double Crimp Female Disconnects - 16-14 Wire, .032x.250 Tab Bulk Bag



Features:


Nylon Fully Insulated Double Crimp Female Disconnects - 16-14 Wire, .032x.250 Tab features include:

- Double Crimp Fully Insulated Female Disconnects feature Nylon Insulation
- Color Coded insulation for easy identification
- Manufactured from High Strength Brass
- Electro-Tin Plated for corrosion resistance
- Easy Entry Expanded Insulation eliminates strand “Hang Up”, increasing crimping rates and provides mechanical strain relief
- Terminal Barrel has Butted Seam
- Serrated Barrel provides excellent electrical contact & resistance to pull-out forces
- Double Crimp Extended Crimp Sleeve provides for multiple crimps resulting in improved electrical contact and pull-out force resistance
- 221°F (105°C) 600 Volts Max
- Maximum Electric Current: 22 AWG - 3 Amp, 20 AWG - 4 Amp, 18 AWG - 7 Amp, 16 AWG - 10 Amp, 14 AWG - 15 Amp, 12 AWG - 20 Amp, 10 AWG - 24 Amp
- cULus Listed
- Dimension Measurements = Inches
- Order Qty of 1000 = 1 Bag of 1000

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts
INSULATION MATERIAL: Nylon
TERMINAL MATERIAL: Electro-Tin Plated Brass
DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps
FEATURES: Serrated Barrel, Expanded Insulation, Oval Housing Shape



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	F	L	B	C	D	T	FIG.	BAG QTY	MASTER BAG QTY
11976B	BLUE	16-14	.032 X .250	.260	.295	.846	.433	.091	.197	.016	1	1,000	10,000