



MORRIS CAT#: 12151
Non-Insulated Parallel Connectors 26-22



Features:

Non-Insulated Parallel Connectors 26-22 Awg features include:

- Non-Insulated Parallel Connector Material: High Strength Electrolytic Tubular Copper
- Electro-Tin Plated for corrosion resistance
- Maximum Electric Current: 22 AWG - 9 Amp, 20 AWG - 12 Amp, 18 AWG - 17 Amp, 16 AWG - 18 Amp, 14 AWG - 30 Amp, 12 AWG - 35 Amp, 10 AWG - 50 Amp
- 302°F(150°C) 600 Volts Max
- cULus Listed
- Dimension Measurements = Inches
- Order Qty of 100 = 1 Bag of 100

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 221°F (150°C) 600V

CONNECTOR MATERIAL: Electro-Tin Plated Tubular Copper

DIMENSIONS = INCHES

<i>CAT. NO.</i>	<i>WIRE SIZE AWG</i>	<i>L</i>	<i>D</i>	<i>DI</i>	<i>BAG QTY</i>	<i>MASTER BAG QTY</i>
12151	26-22	.197	.083	.051	100	1,000