



High Temperature Ring Terminals

MORRIS CAT#'s: 12512-12526



DIMENSIONS = INCHES

| CAT. NO. | WIRE SIZE AWG | STUD SIZE | D2 | W | F | L | E | D | DI | T | BAG QTY | MASTER BOX QTY |
|---------------|---------------|-----------|------|------|------|-------|------|------|------|------|---------|----------------|
| 12512 | 22-16 | 6 | .146 | .260 | .248 | .567 | .189 | .134 | .067 | .030 | 100 | 1,000 |
| 12512B | 22-16 | 6 | .146 | .260 | .248 | .567 | .189 | .134 | .067 | .030 | 1,000 | 20,000 |
| 12514 | 22-16 | 10 | .209 | .315 | .276 | .622 | .189 | .134 | .067 | .030 | 100 | 1,000 |
| 12514B | 22-16 | 10 | .209 | .315 | .276 | .622 | .189 | .134 | .067 | .030 | 1,000 | 20,000 |
| 12515 | 22-16 | 1/4 | .252 | .457 | .433 | .858 | .189 | .134 | .067 | .030 | 1,000 | 10,000 |
| 12516 | 16-14 | 6 | .146 | .260 | .248 | .567 | .189 | .161 | .091 | .031 | 100 | 1,000 |
| 12516B | 16-14 | 6 | .146 | .260 | .189 | .504 | .189 | .161 | .091 | .031 | 1,000 | 20,000 |
| 12518 | 16-14 | 10 | .209 | .335 | .291 | .650 | .189 | .161 | .091 | .031 | 100 | 1,000 |
| 12518B | 16-14 | 10 | .209 | .335 | .291 | .650 | .189 | .161 | .091 | .031 | 1,000 | 20,000 |
| 12520 | 16-14 | 1/4 | .252 | .472 | .433 | .858 | .189 | .161 | .091 | .031 | 100 | 1,000 |
| 12521 | 12-10 | 6 | .146 | .283 | .240 | .618 | .236 | .220 | .134 | .039 | 100 | 1,000 |
| 12522 | 12-10 | 10 | .209 | .374 | .327 | .748 | .236 | .220 | .134 | .039 | 100 | 1,000 |
| 12522B | 12-10 | 10 | .209 | .374 | .327 | .748 | .236 | .220 | .134 | .039 | 1,000 | 10,000 |
| 12523 | 12-10 | 1/4 | .252 | .472 | .413 | .886 | .236 | .220 | .134 | .039 | 100 | 1,000 |
| 12523B | 12-10 | 1/4 | .252 | .472 | .413 | .886 | .236 | .220 | .134 | .039 | 1,000 | 10,000 |
| 12525 | 12-10 | 5/16 | .331 | .591 | .524 | 1.063 | .236 | .220 | .134 | .039 | 100 | 1,000 |
| 12526 | 12-10 | 3/8 | .413 | .591 | .524 | 1.063 | .236 | .220 | .134 | .039 | 100 | 1,000 |
| 12524 | 8 | 1/4 | .252 | .472 | .366 | .937 | .335 | .283 | .177 | .047 | 100 | - |

Features:

- Applications Include: Electric space heaters, HVAC controls, Industrial automation, Commercial ovens and fryers & Industrial kilns
- Material: Nickel Plated Steel
- Temperature Rating: 900°F(482°C)
- Butted Seam
- Order Qty of 100 = 1 Bag of 100