



COLOR SELECTABLE SMALL FLOODS

- 0-10V Dimmable
- Voltage: 120-277V
- Integrated Photocell with On/Off Switch
- Die-Cast Aluminum Housing
- Transparent PC Lens



COLOR TEMPERATURE SELECTABLE &
ON/OFF PHOTOCONTROL



YOKE MOUNT
OPTION INCLUDED



KNUCKLE
PRE-INSTALLED

CAT. NO.	WATTS	MOUNT	HOUSING COLOR	COLOR TEMP	LUMENS @ MAX WATTS	CASE QTY
71531B	15W	1/2" KNUCKLE/ YOKE	BRONZE	3000K 4000K 5000K	2,130	24
71553B	15W	1/2" KNUCKLE/ YOKE	WHITE	3000K 4000K 5000K	2,130	24
71532B	30W	1/2" KNUCKLE/ YOKE	BRONZE	3000K 4000K 5000K	4,440	12
71822B	30W	1/2" KNUCKLE/ YOKE	WHITE	3000K 4000K 5000K	4,440	12

COLOR & WATTAGE SELECTABLE

71533B	40/50/60W	1/2" KNUCKLE/ YOKE	BRONZE	3000K 4000K 5000K	8,950	12
71823B	40/50/60W	1/2" KNUCKLE/ YOKE	WHITE	3000K 4000K 5000K	8,950	12

PLEASE REVIEW ONLINE SPECIFICATION SHEETS. IMAGES AND CERTIFICATIONS MAY NOT BE 100% REPRESENTATIVE OF ALL PRODUCTS LISTED.
TO VIEW DETAILS OF OUR DLC QUALIFIED PRODUCTS, PLEASE CONSULT THE DLC QUALIFIED PRODUCTS LIST AT WWW.DESIGNLIGHTS.ORG/QPL

WWW.MORRISPRODUCTS.COM

1-888-777-6678

