




Morris CAT#: 22532-22548

Nylon Cable Glands - Metric Thread



Features:

- Seal & Clamp System allows cord connector to tighten in a Circular Sequence on the sealing ring to give Superior Strain Relief without twisting or damaging the cable
- Simply push the cable through the liquid-tight nylon strain relief & tighten nut for quick installation
- Threads into your panel for clearance, locknut included
- Internal Ratchet with Self-Locking Feature protects against vibration
- 'Collet' Design Accommodates Various Size Cords, Cables, Tubing, etc.
- Nylon Body Material is resistant to most common chemicals & solvents
- For Best Results, Use the Minimum Size that accommodates your cable
- No Disassembly Required
- Made of UL approved NYLON 66, 94V-2 (Black)
- -22°F to 140°F Temperature Rating
- IP68 Rated Submersible & Dustproof
- Metric Thread - Does not have NPT threading
- UL Recognized - 22534-22542 UR Listed

*Not UL Recognized

DIMENSIONS = INCHES

CAT. NO.	MOUNTING HOLE (D1)	CABLE RANGE	THREAD PITCH (MM)	D2	B1	L1	L2	L3	BAG QTY	MASTER BAG QTY
22532*	.47"	.12-.26"	M12-1.25	.33"	.24"	.31"	.48"	.52"	10	100
22534	.63"	.20-.39"	M16-1.50	.43"	.38"	.62"	.57"	.66"	10	100
22536	.79"	.39-.55"	M20-1.50	.58"	.51"	.59"	.78"	.72"	10	100
22538	.98"	.51-.71"	M25-1.50	.73"	.65"	.59"	.74"	.88"	10	100
22540	1.26"	.71-.98"	M32-1.50	1.02"	.92"	.58"	.80"	1.03"	10	100
22542	1.57"	.87-1.26"	M40-1.50	1.30"	1.20"	.70"	.92"	1.24"	10	100
22544*	1.97"	1.18-1.50"	M50-1.50	1.62"	1.50"	.68"	1.01"	1.24"	10	100
22546*	2.40"	1.34-1.73"	M61-1.50	2.13"	1.73"	.73"	1.06"	1.28"	10	100
22548*	2.48"	1.65-1.97"	M63-1.50	2.20"	1.95"	1.00"	1.16"	1.43"	10	100

www.morrisproducts.com

1-888-777-6678