



MORRIS CAT#: 23002-23004

Luminaire Ballast Disconnects

2-4 Pole



23002

23004

Features:

- 2 & 3 Pole Touch Proof Luminaire Disconnects
- Meets NEC 2008 410.130G & CEC Section 221.-06-Paragraph 30-308(4) Ballast Disconnect Safety Requirements for Non-Residential Fluorescent Fixtures. UL 2459 Compliant
- Patented Push-In Wire Insertion Technology Accommodates both Solid & Stranded Conductors
- Low Insertion Force Eliminates the Need for Installation Tools
- Male/Female Pluggable Touch-Proof Design Provides for Safe Ballast Disconnect Under Load
- Heavy Duty Nylon Housing 105°C Temperature Rating UL 94V-0
- 3A@120V 1.3A@277V .75A@480V

DIMENSIONS = INCHES

CAT. NO.	PORTS LINE	PORTS LOAD	WIRE AWG LINE	WIRE AWG LOAD	VOLTS	L	H	W	BAG QTY	CASE QTY
2 POLE LINE - 2 POLE LOAD										
23002	2	2	12-14	18	120/277	1.32	.86	.45	25	500
2 POLE LINE - 4 POLE LOAD										
23004	2	4	12-18	12-18	120/277	1.46	.75	.50	25	500