



MORRIS CAT#'s: 23284-23486

Wing Connectors



Features:

- Swept wing fits into your hand naturally to give extra torque leverage and reduce the effort required for connecting even large wire combinations, yet compact, with narrow profile to take up less space in junction boxes
- Ribbed cap on color coded wire connectors provide more secure grip and faster fingertip starts even when hands become slippery
- Deep Skirt Entry Provides Protection From FlashOver or Shorting and Keeps Strands from Splaying
- Live Action Square Wire Spring Draws Wires Deep into Spring Provides a More Secure Grip
- No pre-twisting of conductors is required – spring creates its own thread
- Connector Will Bite and Hold on Single Conductor when Capping Isolated Conductor
- Reusable connector threads on or off splice for fast and easy circuit changes and additions
- Tough, Heavy Duty Thick Wall UL 94V-2 Flame Retardant Housing will not crack or break, even when applied to maximum wire combinations under extreme pressure
- Temperature rated at 221°F (105°C) maximum
- 600V, 1000V fixtures & signs



MORRIS CAT#: 23284-23486

Wing Connectors



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE COMBINATIONS	A	B	C	D	E	BOX/BAG QTY	CASE QTY
HANGING BAG SMALL PACK									
23284	YELLOW	MAX: 4 #16 & 2 #18 MIN: 2 #18	252	386	.717	.354	1.016	25	1,250
23285	TAN	MAX: 3 #12 & 3 #18 MIN: 2 #18	283	457	.720	.362	1.142	25	1,250
23286	RED	MAX: 2 #12 & 4 #14 MIN: 1 #16 & 1 #14	.354	.531	.906	.378	1.252	25	1,250
23288	GRAY	MAX: 4 #12 MIN: 2 #10	.394	.587	1.000	.394	1.311	6	1,250
23290	BLUE	MAX: 2 #12 & 3 #10 MIN: 2 #10	472	.740	1.260	.516	1.575	6	1,250
BOXED									
23084	YELLOW	MAX: 4 #16 & 2 #18 MIN: 2 #18	252	386	.717	.354	1.016	100	10,000
23085	TAN	MAX: 3 #12 & 3 #18 MIN: 2 #18	283	457	.720	.362	1.142	100	10,000
23086	RED	MAX: 2 #12 & 4 #14 MIN: 1 #16 & 1 #14	.354	.531	.906	.378	1.252	100	8,000
23088	GRAY	MAX: 3 #10 MIN: 3 #14 & 1 #18	.394	.587	1.000	.394	1.311	50	5,000
23090	BLUE	MAX: 1 #8 & 3 #10 MIN: 2 #10 & 1 #12	472	.740	1.260	.516	1.575	50	4,000
BAGGED BULK PACK									
23184	YELLOW	MAX: 3 #12 MIN: 2 #18	252	386	.717	.354	1.016	500	5,000
23185	TAN	MAX: 3 #10 MIN: 3 #22	283	457	.720	.362	1.142	500	5,000
23186	RED	MAX: 5 #12 MIN: 3 #16	.354	.531	.906	.378	1.252	500	5,000
23188	GRAY	MAX: 3 #10 MIN: 3 #14 & 1 #18	.394	.587	1.000	.394	1.311	100	2,500
23190	BLUE	MAX: 1 #8 & 3 #10 MIN: 2 #10 & 1 #12	472	.740	1.260	.516	1.575	100	1,500
BULK PAIL									
NEW 23194	YELLOW	MAX: 3 #12 MIN: 2 #18	252	386	.717	.354	1.016	-	4,000
NEW 23195	TAN	MAX: 3 #10 MIN: 3 #22	283	457	.720	.362	1.142	-	3,500
NEW 23196	RED	MAX: 5 #12 MIN: 3 #16	.354	.531	.906	.378	1.252	-	2,300
NEW 23197	GRAY	MAX: 3 #10 MIN: 3 #14 & 1 #18	.394	.587	1.000	.394	1.311	-	1,500
NEW 23198	BLUE	MAX: 1 #8 & 3 #10 MIN: 2 #10 & 1 #12	472	.740	1.260	.516	1.575	-	1,000
SMALL JAR									
23384	YELLOW	MAX: 4 #16 & 2 #18 MIN: 2 #18	252	386	.717	.354	1.016	200	6,400
23385	TAN	MAX: 3 #12 & 3 #18 MIN: 2 #18	283	457	.720	.362	1.142	150	4,800
23386	RED	MAX: 2 #12 & 4 #14 MIN: 1 #16 & 1 #14	.354	.531	.906	.378	1.252	100	3,200
LARGE JAR									
23484	YELLOW	MAX: 4 #16 & 2 #18 MIN: 2 #18	252	386	.717	.354	1.016	550	6,600
23485	TAN	MAX: 3 #12 & 3 #18 MIN: 2 #18	283	457	.720	.362	1.142	450	5,400
23486	RED	MAX: 2 #12 & 4 #14 MIN: 1 #16 & 1 #14	.354	.531	.906	.378	1.252	300	3,600