



MORRIS CAT#: 39011-39013

Mechanical Photocontrols - Shutter

Style Spec Grade - Fixed Base



Features:

- Die Cast Aluminum Vandal Resistant Housing
- 1" Extra Wide Light Sensor for Increased Accuracy
- Photocontrol features a heavy-duty thermal bi-metal switch that provides a 30-60 second time delay. This virtually eliminates unwanted lamp cycling that could be caused by lightning, car headlights, etc.
- Although the turn-on level is pre-set at the factory, each control is furnished with an adjustable slide shutter/bar that allows field adjustment
- Typically mount on fixtures or boxes
- Single Pole, Single Throw Switch
- Contact Position at Night is Normally Closed
- Temperature Range: -40°F to 158°F
- Power Consumption Below 1.5 Watts Average
- Standard 1/2" I.P.S. Pipe Threaded Nipple, Includes Gasket and Locknut
- 6" Color Coded Leads with Wiring Diagram on Control
- UL Listed

SPEC GRADE - FIXED BASE

CAT. NO.	VOLTS	TUNGSTEN RATING (W)	BALLAST RATING (VA)	LIGHT SENSOR	CASE QTY	EACH
39011	120V	3000W	3,000VA	1"	50	
39013	208-277V	3000W	3,000VA	1"	50	