



Catalog Number 39040
UPC Number 60198639040
Description Button Style Photocell
Faceplate Included
120 Volt




Features

- Housing: UV stabilized impact resistant Polycarbonate
Includes Faceplate
Heavy-duty thermal bi-metal switch provides a 30+ second time delay
Contact Position at Night is Normally Closed
- Sensor Type: CDS
Single Pole, Single Throw, Normally Closed Switch
Power Consumption Below 1.5 Watts Average
- Load Switching Capability: 5,000 operations
- Load Rated: 600W/1000W/1800VA
3/4" Long 3/8" Threaded Nipple & Nut for 1/2" K.O.
- Operating Temperature: -23°C to +75°C

General

Material: Polycarbonate Housing
Switching: Single Pole, Single Throw NC
Load Rating: 1800W, 1100 VA
Sensor Type: Cadmium Sulfide CDS

Exterior dimension(mm)



Dimension Information

Diameter: 2.15"
Height: 1.7"
Lead: 16AWG/18AWG, LENGTH 6"

Specifications

Temperature Rating: -40°F – +150°F
Voltage Rating: 120 V
Frequency: 50-60 Hertz
Turn-On Light Level: 10-16 Lux
Turn-Off Light Level: <80 Lux
Turn-On Time Delay: 30 sec
Turn-Off Time Delay: 30 sec

Packaging

Bag Qty 1
Master Bag Qty 1

Certifications

UL UL 773 Standard
cUL
RoHS