



MORRIS CAT#: 39060-39062



Photocontrols Pencil Type - Swivel Base



FIG. 1

Features:

- Weatherproof Polycarbonate Housing & Lens
- 1/2" CDS Light Sensor with Heat Sink
- Thermal Switch
- Thin cylindrical shape Swivel Mount Photo Control fits neatly between twin floodlights or other tight applications
- Swivel Mount Photo Controls typically mounts on fixtures or boxes
- Field adjustable swivel base makes it easy to direct the photocell away from stray light
- "O" ring sealed to prevent water from entering through the knuckle
- Light Levels: ON: .9 to 1.9 FC OFF: 2.8 To 5.6 FC
- Single Pole, Single Throw Switch
- Temperature Range: -40°F to 158°F
- Relative Humidity: 96%
- Power Consumption Below: 1.5 Watts Max
- Life Cycle: 6500 Cycles
- Contact Position at Night is Normally Open
- Standard 1/2" I.P.S. Pipe Thread Nipple
- 6" Color Coded Leads with Wiring Diagram on Control
- UL Listed

PENCIL TYPE

CAT. NO.	FIG.	VOLTS	TUNGSTEN RATING (W)	BALLAST RATING (VA)	CASE QTY	EACH
39060	1	120V	1800W	1,100VA	100	
39062	1	208-277V	1800W	1,100VA	100	