



**Catalog Number** 67028  
**UPC Number** 6019867028  
**Description** Epoxy Resin Enapsulation Splice Kts  
In-Line Splice Applications



#### Features

- Exothermic Encapsulating Resin Technology
- Submersible/Direct Burial Rated
- Permanent Watertight Seal Protects against Voltage Leakage, Cable Deterioration, & Cable Failure
- Fast Error-Proof Setup - Low-Viscosity Resin Compound Penetrates Completely Around Splice Penetrates Completely Around Splice
- Rated for Use with Cable Rated to 90°C
- Fungus Resistant
- UL 486D CSA 198.2 Listed
- 600V

#### General

**Material:** Epoxy Resins, Mixing Tube, Mold, Damming Material  
**Wire Range:** 1/0 - 750 MCM

#### Dimension Information

N/A

#### Specifications

Temperature Rating:	90°C		
Dielectric Strength:	at 25°C	> 500 volts/mil	
Dielectric Constant:	at 23°C	3.66 @ 100 Hz	3.52 @ 1KHz
Volume Resistivity:	at 23°C	4.6 x 10 <sup>14</sup> ohm/cm	
Surface Resistivity, ohm	at 23°C	3.8 x 10 <sup>15</sup> ohm/cm	
Dissipation Factor	at 23°C	0.04 @100 Hz	0.03 @ 1KHz
Voltage:		600 Volt	
Cable Rating:		90°C	

#### Packaging

Bag Qty 1

#### Certifications

UL	486D
CSA	198.2