



MORRIS CAT#: 67058, 67060
Direct Burial Mechanical Splice Kits - EPDM
Rubber Cover



Features:

Direct Burial Mechanical Splice Kits - Rubber Cover features include:

- Our Direct Burial Mechanical Splice Kits - Rubber Cover 600 volt max Eliminates expensive crimping tools when splicing Aluminum or Copper conductors for Direct Burial
- Direct Burial and Submersible Rated - Ensures a Water Tight Splice Repair
- Prevents oxidation and keeps out moisture
- Perfect for repairing any 2, 3, or 4 wire installation
- No Taping, Heat Shrink or Mastic Required
- Kit comes complete with one mechanical connector and Rubber Cover
- AL9CU Dual rated For Use with Both Aluminum or Copper Conductors
- Popular splicing applications would be for repair and/or extending type USE cable and other electrical cables
- Splice kit contains UL Listed Components
- 600 Volt maximum 221°F (105°C) rating
- ANSI C119.4 Compliant RUS Approved
- Order Qty of 1 = 1 Kit

DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE AWG	SCREW CONFIGURATION	CONNECTOR (INCHES)		COVER (INCHES)		CASE QTY
			DIA.	L.	DIA.	L.	
67058	#6-350 MCM	2 SCREW	1.13	2.56	1.55	10.45	25
67060	#6-350 MCM	4 SCREW	1.13	4.06	1.55	10.45	25