



Streetlighting In-Line Mechanical Breakaway Disconnect Kits

MORRIS CAT#'s: 67064-67065



CAT#: 67064



CAT#: 67065

Kit Includes:

EPDM Rubber Housing, Fuse Clips,
Connecting Link (as Required),
Silicone Lubricant. Fuse Not Included.

CAT. NO.	FUSED/ NON-FUSED	WIRE RANGE RUN	WIRE RANGE TAP	DIMENSIONS (INCHES)		CASE QTY
				DIA.	L	
67064	FUSED	#12-#4	#12-#4	1-1/16	5-3/8	25
67065	NON-FUSED	#12-#4	#12-#4	1-1/16	5-3/8	25

Features:

1. Street-lighting In-Line Mechanical Breakaway Disconnect Kit separated from Base under Impact
2. Designed for Use in Streetlight Hand Holes
3. Completely Waterproof Rubber Over-molded Insulated Body Ensures Installer Safety and Connector Integrity
4. Fuse or Connecting Link Remains in Load Side of Light Pole When Separated
5. Range Taking Design Covers a Wide Range of Wire Sizes Thru .38" Diameter using a Stepped "ROCKET" Sealing Feature
6. 67064 Accepts Standard Cartridge Fuses 13/32" X 1-1/2" - No Glass Fuses
7. AL9CU Dual Rated for Both Copper and Aluminum Cables
8. Eliminates the Need for Taping, Heat Shrink and other Labor Intensive Insulating Methods
9. 30 Amp
10. 600 Volts
11. Kits Include: EPDM Rubber Housing, Fuse Clips, Connecting Link(as Required), Silicone Lubricant. - Fuse Not Included
12. Order Qty of 1 = 1 Piece