



**MORRIS CAT#: 68040**  
**Thin Wall Heat Shrink Tubing .367"-.176" 6" Black**



**Features:**

Thin Wall Heat Shrink Tubing .367"-.176" 6" Black features include:

- Heat Shrink Tubing used for Electrical Insulation, Wire Harness, Bundling, Splices & Terminations
- Flexible Polyolefin Tubing
- 2:1 Shrink Ratio
- Rated for 600 Volt 257°F (125°C) continuous operation
- Heat Shrink Tubing forms Tough, Smooth Insulated Covering resistant to common fluids and solvents
- UL224 Recognized/CSA Listed
- Order Qty of 10 = 1 Bag of 10

DIMENSIONS = INCHES

<b>CAT NO.</b>	<b>LENGTH</b>	<b>COLOR</b>	<b>DIAMETER BEFORE SHRINKING</b>	<b>DIAMETER AFTER SHRINKING</b>	<b>BAG QTY</b>
68030	6"	BLACK	.078	.029	50
68032	6"	BLACK	.098	.039	50
68034	6"	BLACK	.137	.059	50
68036	6"	BLACK	.211	.098	10
68038	6"	BLACK	.250	.117	10
68040	6"	BLACK	.367	.176	10
68042	6"	BLACK	.484	.234	10
68044	6"	BLACK	.827	.390	10
68046	6"	BLACK	1.26	.590	10