



MORRIS CAT#: 68062
Thin Wall Heat Shrink Tubing .484"-.234" 165'
Reels Black



Features:

Thin Wall Heat Shrink Tubing On Reels .484"-.234" 165' Reels Black features include:

- Heat Shrink Tubing used for Electrical Insulation, Wire Harness, Bundling, Splices & Terminations
- Flexible Polyolefin Tubing
- 2:1 Shrink Ratio
- Rated for 600 Volt 257°F (125°C) continuous operation
- Heat Shrink Tubing forms tough, smooth insulated covering resistant to common fluids and solvents
- UL224 Recognized/CSA Listed
- Order Qty of 1 = 1 Roll

DIMENSIONS = INCHES

<i>CAT NO.</i>	<i>LENGTH</i>	<i>COLOR</i>	<i>DIAMETER BEFORE SHRINKING</i>	<i>DIAMETER AFTER SHRINKING</i>	<i>BAG QTY</i>
68056	330 FT	BLACK	.211	.098	1 ROLL
68058	330 FT	BLACK	.250	.117	1 ROLL
68060	165 FT	BLACK	.367	.176	1 ROLL
68062	165 FT	BLACK	.484	.234	1 ROLL
68064	165 FT	BLACK	.827	.390	1 ROLL
68066	165 FT	BLACK	1.26	.590	1 ROLL