# MORRIS CAT#: 68084
# Thin Wall Heat Shrink Tubing .484"-.234" 4' Black



**Features:**

Thin Wall Heat Shrink Tubing .484"-.234" 4' Black features include:

- Heat shrink tubing used for electrical insulation, wire harness, bundling, splices & terminations
- Flexible Polyolefin Tubing
- 2:1 Shrink Ratio
- Rated for 600 Volt 257°F (125°C) continuous operation
- Heat shrink tubing forms tough, smooth insulated covering resistant to common fluids and solvents
- UL224 Recognized/CSA Listed
- Order Qty of 1 = 1 Piece

DIMENSIONS = INCHES

| CAT NO. | LENGTH | COLOR | DIAMETER BEFORE SHRINKING | DIAMETER AFTER SHRINKING | BAG QTY |
|---|---|---|---|---|---|
| 68072 | 4 FT | BLACK | .078 | .029 | 1 |
| 68074 | 4 FT | BLACK | .098 | .039 | 1 |
| 68076 | 4 FT | BLACK | .137 | .059 | 1 |
| 68078 | 4 FT | BLACK | .211 | .098 | 1 |
| 68080 | 4 FT | BLACK | .250 | .117 | 1 |
| 68082 | 4 FT | BLACK | .367 | .176 | 1 |
| 68084 | 4 FT | BLACK | .484 | .234 | 1 |
| 68086 | 4 FT | BLACK | .827 | .390 | 1 |
| 68088 | 4 FT | BLACK | 1.26 | .590 | 1 |