MORRIS CAT#: 68088
Thin Wall Heat Shrink Tubing 1.26"-.590" 4' Black



Features:

Thin Wall Heat Shrink Tubing 1.26"-.590" 4' Black features include:

- Heat shrink tubing used for electrical insulation, wire harness, bundling, splices & terminations
- Flexible Polyolefin Tubing
- 2:1 Shrink Ratio
- Rated for 600 Volt 257°F (125°C) continuous operation
- Heat shrink tubing forms tough, smooth insulated covering resistant to common fluids and solvents
- UL224 Recognized/CSA Listed
- Order Qty of 1 = 1 Piece

DIMENSIONS = INCHES

CAT NO.	LENGTH	COLOR	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	BAG QTY
68072	4 FT	BLACK	.078	.029	1
68074	4 FT	BLACK	.098	.039	1
68076	4 FT	BLACK	.137	.059	1
68078	4 FT	BLACK	.211	.098	1
68080	4 FT	BLACK	.250	.117	1
68082	4 FT	BLACK	.367	.176	1
68084	4 FT	BLACK	.484	.234	1
68086	4 FT	BLACK	.827	.390	1
68088	4 FT	BLACK	1.26	.590	1