



MORRIS CAT#: 68146
Medium Wall Heat Shrink Tubing- 3:1 Shrink
Ratio 25' 1.10"-.400" 2-4/0



Features:

Medium Wall Heat Shrink Tubing 25' 1.10"-.400" 2-4/0 features include:

- 3:1 Shrink Ratio
- Heat Shrink Tubing that is suitable for a variety of Low Voltage (2500 Volt and Below) Electrical and Mechanical Applications, where lighter weight and greater flexibility are important
- Seals and Protects Cable Splices and Terminations
- High Resistance to Impact and Abrasion
- 4' Medium Wall Heat Shrink Tubing has Thermoplastic Adhesive Liner for Complete Environmental Protection and Insulation
- Continuous Operating Temperature: -67°F to 230°F (-55°C to 110°C)
- Shrink temperature: 248°F (120°C)
- Medium Wall Heat shring Tubing is rated for 600-2500V
- Black Color
- Order Qty of 1 = 1 Piece

DIMENSIONS = INCHES

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
ROLLS					
68142	12-6		.40	.15	.080
68144	8-1/0		.75	.22	.080
68146	2-4/0		1.10	.40	.080
68148	3/0-400		1.50	.50	.080
68150	-	50 FT	1.70	.50	.080
68152	250-750	25 FT	2.05	.75	.080
68154	800-1250	25 FT	3.50	1.18	.095
68156	1500-2500	50 FT	4.70	1.57	.105