




MORRIS CAT#: 70252
Heavy Duty Momentary Contact Toggle Switch
SPST On-(Off) Screw Terminals



Features:

Heavy Duty Momentary Contact Toggle Switch SPST On-(Off) Screw Terminals features include:

- Motor Control & Tool Applications
- Momentary = ()
- SPST, On-(Off)
- 2 Screw Terminals
- 20 AMP, 125VAC
- 10 AMP, 277VAC
- 3/4HP 125/250VAC
- Solid Brass or Nickel Plated Bushings
- 1/2" Mounting Hole
- Dielectric Strength: 1500V
- Mechanical Life Cycles: 100,000
- Operating Temperature: 32°F to 185°F
- cURus Listed
- Order Qty of 1 = 1 Piece

CAT. NO.	POLES	FUNCTION	TERMINAL TYPE	NO. OF TERMINALS	STANDARD LOAD RATING	MOTOR LOAD RATING	DIMENSIONS L" X W" X H"	BAG QTY	MASTER BAG
SINGLE POLE SINGLE THROW									
70252	SPST	MOMENTARY ON-(OFF)	SCREW	2	20A 125VAC 10A 277VAC	20A 125VAC 10A 250VAC 3/4HP 125-250VAC	1.13 X .57 X .61	1	10