


4" 15W COMMERCIAL DOWNLIGHT










Part#	Housing Color	Wattage	Lumens	ССТ	Voltage	Input Current @ 120V	Lumens/ Watt	Energy Star
72656	White	15W	1138	3000K	120	.1286A	76	Yes





4" 15W COMMERCIAL DOWNLIGHT

Construction:

White Trim

Technical Specifications:

Frequency: 60Hz

50,000+ LED Life Span

BUG Rating: N/A

CRI: ≥ 91

Chromacity Measurements:

Chromaticity (u,v): u=.2627; v= .3529

15 Watts

Electrical: Operating Temperature:

Input Voltage: 120 Minimum Starting -31° - 122° F

Current: .1286A @ 120V

Power Factor: ≥.95 Housing: Aluminum Housing

Product Parameters: IP Rating: IP43 Wet Indoor Location Rated

Efficacy: 76 lumens per watt

Lens Material: Frosted Polycarbonate Lens

CCT: 3000k (Warm White)

Mounting: Ceiling Mount

(Drywall / Sheetrock)

Beam Angle: 60° Listings: UL, Energy Star

R9: 39 Carton Qty: 1
DUV: 0.00119 Weight: 7 lb

Chromaticity (x,y): x=.4629; y= .4145

Weight: 7 lb

Warranty:

Morris Products carries a 5 year warranty from date of purchase

against defects in materials and workmanship (assuming normal and proper usage).

Component Specifications:

LED: SMD 2835

Driver: 120V 50HZ

Driver Output Volts:

Driver Output Amps:

Dimming: Tri-ACK Dimming

Surge Protection: 2500V