



**Catalog Number** 73512  
**UPC Number** 60198673512  
**Description** Standard with Self Diagnostic Exit Sign  
LED  
Red Letters White Housing

#### Features

- Superior Quality Exit Unit Combined with LED Energy Saving Technology
- Completely Self-Contained
- Fully Automatic Operation
- Compact, Low Profile Design in Neutral Finish
- Push to Test Switch in Battery Backup Units
- Automatic, Low Voltage Disconnect (LVD)
- 120 or 277 VAC Operation
- Injection-Molded, UL 94 V-0 Flame Retardant, High Impact Housing
- Charge Rate/Power On LED Indicator Light
- LED Life Expectancy of 50,000+ Hours
- Energy Consumption of Less than 4 Watts for Red Letters and Less than 2 Watts for Green Letters
- Listed for Damp Location
- Universal Mounting Canopy & 2 Face Plates for Side or

#### Top Installation

- 400MAH 3.6V Ni-CAD Battery
- 90 Minute Battery Run Time
- Self Diagnostic Features:  
On-Line real time monitoring of battery charging, disconnection or failure and local or remote lamp failure  
Self Testing and 15 Minute discharge every 30 days  
Self Testing and 90 Minute discharge annually

#### Dimension Information

|                   |       |
|-------------------|-------|
| L Inches          | 12.00 |
| H Inches          | 7.50  |
| Depth Inches (mm) | 1.50  |

#### Specifications

|                      |                                          |
|----------------------|------------------------------------------|
| Input Rating Amps:   | 18.1 mA @120V, 7.76 mA @ 277V            |
| Input Rating Watts:  | 1.64W @ 120V 1.60W @ 277V                |
| Frequency:           | 60 Hz                                    |
| Voltage Rating:      | 120/277                                  |
| Flammability Rating: | UL94V-0                                  |
| Battery Operation:   | 3.6 Volt 400 mAh Ni-Cad - 90 Minutes Min |

#### Packaging

|                   |   |
|-------------------|---|
| Box Qty           | 1 |
| Master Carton Qty | 6 |

#### Certifications

|      |        |
|------|--------|
| UL   | UL 924 |
| cUL  | No     |
| RoHS | Yes    |

#### Warranty

Five Years

