Catalog Number See Table
UPC Number
Description Dual Rated Aluminum Split Bolt
#6 Thru 2/0
UL467 DB Listed




Features

- Manufactured from High Strength High Conductivity Copper Alloy
- Electro-Tin Plated
- CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
- Conductor Spacer to accommodate dissimiliar conductors

General

Conductor Size:	#6 to 4/0
Material:	Cast Copper Alloy
Finish:	Electro-Tin Plating



Dimension Information

Stock Thickness	See Table

Specifications

Temperature Rating	75^0 C
Voltage Rating	600
Flammability Rating	N/A
Amp Rating	To Conductor

Packaging

Box Qty	See Table

Certifications

UL	UL 467 Listed For Direct Burial
CSA	Yes
RoHS	N/A

Cat No.	AWG	Max Run To Max Tap	Min Run To Min Tap	Max Run To Min Tap	Min Equal Tap & Run	Temp Rating	Torque In-Lb	B	C	H	L	R	V	W	Box Qty	
90412	6	4-4	8-14	4-14	8-8	75^0C	165	0.492	0.625	0.83	1.06	0.413	0.165	0.722	100	
90414	4	4-4	6-14	4-14	8-8	75^0C	165	0.709	0.812	1.04	1.24	0.579	0.268	0.938	50	
90416	2	2-2	2-14	2-14	6-6	75^0C	275	0.748	0.812	1.13	1.44	0.614	0.326	0.938	50	
90418	1/0	1/0-1/0	1-14	1/0-14	4-4	75^0C	385	0.787	0.937	1.25	1.73	0.708	0.374	1.08	50	
90420	2/0	2/0-2/0	2-6	2/0-14	2-2	75^0C	385	0.866	1.06	1.3	1.71	0.807	0.421	1.23	25	

90422
90424
90426

36617	4/0-4/0	40580	4/0-6		90°C	500	1.17	1.5	1.13	2.75	1.17	0.56	1.73	30	
350	350-350	1/0-4	350-4		90°C	650	1.66	1.68	1.48	2.99	1.5	0.696	1.93	12	
500	500-500	400-2	500-2		90°C	825	1.95	2.1	1.7	3.29	1.71	0.85	2.3	12	