



MORRIS CAT#: 90671 - 90696

Insulated Service Entrance Compression Splices

2-25/32" 5/8 Die



Features:

- For Standard Conductors
- High Conductivity Insulated Service Entrance Splice meets or exceed Class A-3 requirements of ANSI C119.4, when properly installed on Aluminum to Aluminum or Aluminum to Copper Conductors
- High Conductivity Aluminum Service Entrance Splices have Solid Center Barriers and Large Chamfers to ease cable insertion
- High Conductivity Splice is coated with Oxide Inhibiting compound
- Tough Stabilized Nylon Sleeve resists installation tool pressure, providing reliable 600 Volt insulation
- Color coded and marked with catalog numbers, strip lengths, installing die references and compression locations
- RUS Approved
- ANSI C119.4 Compliant

2-25/32" LENGTH 5/8" DIE

DIMENSIONS = INCHES

CAT. NO.	MODEL#	COLOR	CONDUCTOR A AL OR CU					CONDUCTOR B AL OR CU					BOX QTY	
			ACSR	STR	SOL	DIA. MAX	DIA. MIN	COLOR	SOL	STR	ACSR	DIA. MAX		DIA. MIN
90696	UGG 88	GREEN	-	#8	#6	.162	.144	GREEN	#6	#8	-	.162	.144	100
90691	UBBR 61							BROWN	#8	#10	-	.128	.114	100
90692	UBG 68	BLUE	#6	#6	#4	.204	.184	GREEN	#6	#8	-	.162	.144	100
90694	UBB 66							BLUE	#4	#6	#6	.204	.184	100
90685	UOBR 41							BROWN	#8	#10	-	.128	.114	100
90686	UOG 48	ORANGE	#4	#4	#2	.258	.213	GREEN	#6	#8	-	.162	.144	100
90690	UOB 46							BLUE	#4	#6	#6	.204	.184	100
90688	UOQ 44							ORANGE	#2	#4	#4	.258	.213	100
90676	URBR 21							BROWN	#8	#10	-	.128	.114	100
90677	URG 28							GREEN	#6	#8	-	.162	.144	100
90684	URB 26	RED	#2	#1 & #2	-	.328	.268	BLUE	#4	#6	#6	.204	.184	100
90678	URO 24							ORANGE	#2	#4	#4	.258	.213	100
90680	URR 22							RED	-	#1 & #2	#2	.328	.268	100
90671	UYG 08							GREEN	#6	#8	-	.162	.144	100
90673	UYB 06							BLUE	#4	#6	#6	.204	.184	100
90674	UYD 04	YELLOW	1/0	1/0	-	.398	.368	ORANGE	#2	#4	#4	.258	.213	100
90672	UYR 02							RED	-	#1 & #2	#2	.328	.268	100
90675	UYV 00							YELLOW	-	1/0	1/0	.398	.368	100