



Morris CAT#: 90732-90736B
One Conductor Two Hole Mount -
Aluminum Mechanical Lug



FIG 3

Features:

- Manufactured from High Strength 6061-T6 Aluminum Alloy to Insure Both Maximum Strength and Conductivity
- Dual Rated for both Copper and Aluminum Conductors
- Electro-Tin Plated for Low Contact Resistance and Protection Against Corrosion
- Assembly can be Made With Only a Screwdriver or Allen Wrench
- Connectors are Re-Usable
- NEMA Standard 1-3/4" Center Hole Spacing
- Rated 600V; 194°F (90°C)
- UL486B LISTED AL9CU

DIMENSIONS = INCHES

CAT. NO.	AWG	FIG	WIRE RANGE	LENGTH	WIDTH	HEIGHT	STUD SIZE	BOX QTY
ONE CONDUCTOR - TWO HOLE MOUNT								
90732	350	3	350MCM-6SOL.	1.13	1.13	1.25	0.50	15
90733	500	3	500MCM-4SOL.	4.22	1.50	1.57	0.50	6
90734	600	3	600MCM-2SOL.	4.22	1.50	1.57	0.50	5
90734B	600	3	600MCM-2SOL.	4.22	1.50	1.57	0.50	100
90735	800	3	800MCM-300MCM	4.62	1.75	1.94	0.50	5
90735B	800	3	800MCM-300MCM	4.62	1.75	1.94	0.50	100
90736	1000	3	1000MCM-500MCM	4.62	1.75	1.94	0.50	5
90736B	1000	3	1000MCM-500MCM	4.62	1.75	1.94	0.50	80



Morris CAT#: 90732-90736B
One Conductor Two Hole Mount -
Aluminum Mechanical Lug

Torque Chart

Tightening Torque Slotted Screws (in-lbs.)

Per UL486A/B Table 23

<i>Wire Size</i>	<i>Torque</i>
#2-2/0	50
#4-#6	45
#8	40
#10-#14	35

Torque Chart

Tightening Torque Internal Hex Screws (in-lbs.)

Per UL486A/B Table 23

<i>Connector Size</i>	<i>Torque</i>
1000	600
750-800	500
500-600	375
250-350	275
1/0-2/0	120