



Catalog Number See Table
UPC Number
Description Three Conductor Two or Four Hole Mount Aluminum Mechanical Lug

- Features**
- Manufactured from High Strength High Conductivity Aluminum Alloy
 - Electro-Tin Plated
 - CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
 - Two Conductor Two Hole or Four Hole Configuration

General
Conductor Size: See Table
Material: 6061-T6 Aluminum Alloy
Finish: Electro-Tin Plating
Screw Type: Hex Head
Wire Range: 300 Thru 1000 MCM

Dimension Information
 See Table

Specifications
Temperature Rating 90° C
Voltage Rating 600
Flammability Rating N/A
Amp Rating To Conductor

Packaging
Box Qty See Table

Certifications
 UL UL 486B UL41968 CU9AL Dual Rated
 CSA LR 27194
 RoHS Yes

Cat No.	AWG	Fig.	Wire Range	Box Qty	L	W	H	Bolt	
THREE CONDUCTORS - TWO & FOUR HOLE MOUNT									
90852	300	7	250MCM - 6SQL	3	4	2.81	1.19	0.56	
90854	350	7	350MCM - 6SQL	1	4.31	3	1.38	0.56	
90858	600	7	600MCM - 4SQL	1	4.5	3.75	1.56	0.56	
90860	750	7	800MCM - 300MCM	1	4.75	4.5	1.75	0.56	
90862	1000	7	1000MCM - 500MCM	1	4.75	4.5	1.75	0.56	