



Morris CAT#: 90924-90926B
**Panelboard Lugs Four Conductors -
 Dual Rated Aluminum Mechanical Panelboard Lugs**



FIG 4

Features:

- Manufactured from High Strength 6061-T6 Aluminum Alloy to Insure Both Maximum Strength and Conductivity
- Dual Rated for both Copper and Aluminum Conductors
- Electro-Tin Plated for Low Contact Resistance and Protection Against Corrosion
- Assembly can be Made With Only a Screwdriver or Allen Wrench
- Connectors are Re-Usable
- Rated 600V; 194°F (90°C)
- UL486B LISTED AL9CU

DIMENSIONS = INCHES

CAT. NO.	AWG	FIG	WIRE RANGE	LENGTH	WIDTH	HEIGHT	HOLE SPACE	STUD SIZE	BOX QTY
PANELBOARD LUGS - FOUR CONDUCTORS									
90924	600	4	600MCM-2STR.	4.92	2.70	3.00	1.38	0.375	2
90924B	600	4	600MCM-2STR.	4.92	2.70	3.00	1.38	0.375	24
90926	750	4	750MCM-1/0STR.	4.92	2.80	3.00	1.38	0.375	2
90926B	750	4	750MCM-1/0STR.	4.92	2.80	3.00	1.38	0.375	24

www.morrisproducts.com

1-888-777-6678



Morris CAT#: 90924-90926B
Panelboard Lugs Four Conductors -
Dual Rated Aluminum Mechanical Panelboard Lugs

Torque Chart

Tightening Torque Slotted Screws (in-lbs.)

Per UL486A/B Table 23

<i>Wire Size</i>	<i>Torque</i>
#2-2/0	50
#4-#6	45
#8	40
#10-#14	35

Torque Chart

Tightening Torque Internal Hex Screws (in-lbs.)

Per UL486A/B Table 23

<i>Connector Size</i>	<i>Torque</i>
1000	600
750-800	500
500-600	375
250-350	275
1/0-2/0	120