



Morris CAT#: 90964-90968
Four Conductors Four Hole Mount -
Aluminum Mechanical Lug



FIG 13

Features:

- Manufactured from High Strength 6061-T6 Aluminum Alloy to Insure Both Maximum Strength and Conductivity
- Dual Rated for both Copper and Aluminum Conductors
- Electro-Tin Plated for Low Contact Resistance and Protection Against Corrosion
- Assembly can be Made With Only a Screwdriver or Allen Wrench
- Connectors are Re-Usable
- NEMA Standard 1-3/4" Center Hole Spacing
- Rated 600V; 194°F (90°C)
- UL486B LISTED AL9CU

DIMENSIONS = INCHES

<i>CAT. NO.</i>	<i>AWG</i>	<i>FIG</i>	<i>WIRE RANGE</i>	<i>LENGTH</i>	<i>WIDTH</i>	<i>HEIGHT</i>	<i>STUD SIZE</i>	<i>BOX QTY</i>
FOUR CONDUCTORS - FOUR HOLE MOUNT								
90964	250	I3	250MCM-6SOL.	5.00	3.30	1.02	0.56	2
90966	600	I3	600MCM-2SOL.	5.58	5.00	1.62	0.50	2
90967	800	I3	800MCM-350MCM	5.58	5.51	1.94	0.50	2
90968	1000	I3	1000MCM-350MCM	4.62	5.97	1.94	0.50	2



Morris CAT#: 90964-90968
Four Conductors Four Hole Mount -
Aluminum Mechanical Lug

Torque Chart

Tightening Torque Slotted Screws (in-lbs.)

Per UL486A/B Table 23

<i>Wire Size</i>	<i>Torque</i>
#2-2/0	50
#4-#6	45
#8	40
#10-#14	35

Torque Chart

Tightening Torque Internal Hex Screws (in-lbs.)

Per UL486A/B Table 23

<i>Connector Size</i>	<i>Torque</i>
1000	600
750-800	500
500-600	375
250-350	275
1/0-2/0	120