



Morris CAT#: 91716

I-BEAM GROUND CLAMP



Features:

- Connects Ground Conductor to I-Beam or other Metal Framing
- Connects 1 Ground Wire to 1/4" Thick Bar or Stanchion
- Popular for Cable Tray, Fence Posts and Structural Steel
- Lay-In Feature for use with Continuous Grounding Loops
- Cast of High Strength High Conductivity Copper Alloy
- Stainless Steel Bolts, Nuts and Lock Washers
- UL 467 Listed for Direct Burial Grounding/ Bonding Applications in Soil and Concrete
- cULus Listed
- Dimension Measurements = Inches
- Order Qty of 1 = 1 Piece

DIMENSIONS = INCHES

| CAT. NO. | FIG | CONDUCTOR RANGE | | DIMENSIONS | | | BOLT SIZE | BOX QTY |
|---|-----|-----------------|---------|------------|-------|--------|-----------|---------|
| | | MIN | MAX | LENGTH | WIDTH | HEIGHT | | |
| GROUND CONDUCTOR ISOLATED FROM BAR | | | | | | | | |
| 91715 | I | 8 SOL | 4 STR | 1-1/4 | 1 | 1-5/8 | 3/8 | 25 |
| 91716 | I | 4 SOL | 2/0 STR | 1-5/8 | 1-1/8 | 1-3/4 | 3/8 | 10 |
| 91717 | I | 2/0 SOL | 250 MCM | 2-1/8 | 1-1/2 | 2 | 1/2 | 10 |

1-888-777-6678

www.morrisproducts.com