



MORRIS CAT#: 91819 - 91825
C-Taps - Copper - Heavy Wall



Features:

- Copper C Taps are UL 467 Listed for Direct Burial & Grounding/Bonding Applications
- Applications include Copper To Copper Splice/Tap or Stub/Pigtail Connections and Grounding
- Allows for 2 Continuous Parallel Conductors
- Heavy Wall High Strength Electrolytic Copper
- Compact Size
- Range Taking
- 600 volt
- UL/CSA Listed

DIMENSIONS = INCHES

CAT. NO.	CONDUCTOR RANGE		DIE TYPE	DIMENSIONS					STRIP LENGTH	BOX QTY
	RUN MAX	TAP MAX		L (OD)	L (ID)	W	D	ENTRY		
91819	6-6	6-6	BG	.77	.46	.71	.43	.29	3/4	50
91820	6-4	4-4	BG	.81	.53	.63	.47	.31	3/4	25
91821	2-2	8-4	C	.98	.65	.75	.61	.37	3/4	50
91822	2-2	2-2	C	1.05	.76	.76	.60	.45	3/4	50
91823	1/0-2/0	1/0-2/0	C	1.35	.87	.95	.80	.43	1-1/8	25
91824	3/0-4/0	1/0-2/0	D3	1.64	1.01	1.07	.97	.60	1-1/4	15
91825	3/0-4/0	3/0-4/0	D3	1.58	1.10	1.07	.97	.56	1-1/4	15