MORRIS CAT#: 94649-94685
Copper Flex Cable Long Barrel
1 Hole Compression Lugs



Features:

- High Conductivity Seamless Copper
- Electro-Tin Plating Resists Corrosion, Reduces Contact Resistance for Maximum Conductivity
- Flared/Belled Entry for Easy Insertion of Fine Strand Flexible Cable - Class G, H, I, K (Battery), M (Welding), DLO
- Color Coded Die Index and Crimp Marks Printed on Barrel
- UL 486A Listed for Applications Thru 35KV

DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE	STUD SIZE	COLOR CODE	COMM	ASTM CLASS H	WELDING CLASS M	DLO	A	A1	B	C	D	E	F	F1	F2	BOX QTY
94650	8	1/4	RED	8	10	10	-	1.52	.81	.42	.08	.25	.28	.59	.12	.32	50
94652	6	#10	BLUE	6	8	8	(61)	1.77	.98	.42	.08	.21	.30	.67	.16	.34	50
94653	6	1/4	BLUE	6	8	8	(61)	1.77	.98	.42	.08	.25	.30	.67	.16	.34	50
94656	4	10	GRAY	4	6	6	(105)	1.77	.98	.49	.09	.21	.31	.67	.16	.42	50
94657	4	1/4	GRAY	4	6	6	(105)	1.77	.98	.49	.09	.25	.31	.67	.16	.42	50
94659	4	5/16	GRAY	4	6	6	(105)	1.77	.98	.49	.09	.33	.31	.67	.16	.42	50
94660	2	#10	BROWN	2	4	4	(125)	2.07	1.10	.60	.10	.21	.37	.81	.18	.49	25
94661	2	5/16	BROWN	2	4	4	(125)	2.07	1.10	.60	.10	.33	.37	.81	.18	.49	25
94662	1	#10	GREEN	1	2	2	(150)	2.11	1.10	.67	.11	.21	.37	.81	.18	.53	25
94663	1	5/16	GREEN	1	2	2	(150)	2.11	1.10	.67	.11	.33	.37	.81	.18	.53	25
94664	1/0	#10	PINK	1/0	1	1	(225)	2.21	1.20	.74	.13	.21	.37	1.06	.18	.56	10
94649	1/0	1/4	PINK	1/0	1	1	(225)	2.21	1.20	.74	.13	.25	.37	1.06	.18	.56	10
94665	1/0	5/16	PINK	1/0	1	1	(225)	2.21	1.20	.74	.13	.33	.37	1.06	.18	.56	10
94666	1/0	3/8	PINK	1/0	1	1	(225)	2.21	1.20	.74	.13	.41	.37	1.06	.18	.56	10
94667	1/0	1/2	PINK	1/0	1	1	(225)	2.50	1.20	.74	.13	.51	.47	1.06	.18	.56	10
94651	2/0	1/4	BLACK	2/0	1/0	1/0	1/0(275)	2.68	1.38	.81	.12	.25	.47	1.06	.18	.64	10
94668	2/0	3/8	BLACK	2/0	1/0	1/0	1/0(275)	2.68	1.38	.81	.12	.41	.47	1.06	.24	.64	10
94669	2/0	1/2	BLACK	2/0	1/0	1/0	1/0(275)	2.68	1.38	.81	.12	.51	.47	1.06	.24	.64	10
94670	3/0	3/8	ORANGE	3/0	2/0	-	2/0(325)	2.80	1.38	.90	.13	.41	.47	1.06	.24	.72	10
94671	3/0	1/2	ORANGE	3/0	2/0	-	2/0(325)	2.80	1.38	.90	.13	.51	.47	1.06	.24	.72	10
94673	4/0	3/8	PURPLE	4/0	3/0	2/0	3/0(450)	2.80	1.42	1.00	.13	.51	.52	1.06	.26	.77	10
94674	4/0	1/2	PURPLE	4/0	3/0	2/0	3/0(450)	2.80	1.42	1.00	.13	.51	.52	1.06	.26	.77	10
94676	250	1/2	YELLOW	250	-	3/0	4/0(550)	3.03	1.61	1.09	.15	.51	.52	1.06	.26	.84	10
94677	300	1/2	WHITE	300	4/0	4/0	262.6	3.39	1.97	1.19	.15	.51	.52	1.06	.31	.94	10
94678	350	1/2	RED	350	250	250	313.1	3.46	1.97	1.28	.17	.51	.52	1.06	.33	1.02	10
94679	350	5/8	RED	350	250	250	313.1	3.46	1.97	1.28	.17	.67	.51	1.06	.33	1.02	10
94680	400	1/2	BLUE	400	300	300	350	3.86	1.97	1.39	.18	.51	.51	1.38	.33	1.08	10
94681	400	5/8	BLUE	400	300	300	350	3.86	1.97	1.39	.18	.67	.51	1.38	.33	1.08	10
94683	500	5/8	BROWN	500	350	350	373.3	4.13	2.24	1.54	.22	.67	.51	1.38	.35	1.20	10
94684	600	5/8	GREEN	600	400	400	444.4	4.25	2.24	1.72	.25	.67	.69	1.46	.39	1.34	6
94685	750	5/8	BLACK	750	600	500	-	5.16	2.64	1.90	.27	.67	.69	1.85	.43	1.47	3