



Catalog Number See Table
UPC Number
Description Insulated Mechanical Connector
 Multi-Cable Bi-Directional Entry
 Clear Insulation



Features

- Insulated Mechanical Connector - Clear PVC Insulation
- Multi-Tap Bi-Directional Conductor Entry
- Aluminum Mechanical Connector
- AL/CU Dual Rated
- Gutter, Raceway, Enclosure Power Distribution Applications

General

Material: 60601-T6 Plated Aluminum
Insulation: Clear Abrasion & Chemical Resistant PVC Insulation
Bolt: Hex Head
Wire Range: #14 - 500 MCM
 Prefilled Oxide Inhibitor

Dimension Information

See Table

Specifications

Temperature Rating 49°F - 194°F
Voltage Rating 600
Flammability Rating N/A
Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL 486B Dual Rated CU9AL ANSI C119.4
cUL Yes
RoHS N/A

| Cat No. | No. of Ports | Wire Range | Length | Width | Height | Box Qty |
|---------|--------------|-------------|--------|-------|--------|---------|
| 97312 | 2 | 4-14 | 1.13 | 1.63 | 1.31 | 12 |
| 97314 | 3 | 4-14 | 1.56 | 1.63 | 1.31 | 12 |
| 97316 | 4 | 4-14 | 2.06 | 1.63 | 1.31 | 6 |
| 97318 | 5 | 4-14 | 2.56 | 1.63 | 1.31 | 6 |
| 97320 | 6 | 4-14 | 3.06 | 1.63 | 1.31 | 6 |
| 97322 | 8 | 4-14 | 4.06 | 1.63 | 1.31 | 4 |
| 97352 | 2 | 2/0 - 14 | 1.63 | 1.75 | 1.38 | 6 |
| 97354 | 3 | 2/0 - 14 | 2.38 | 1.75 | 1.38 | 6 |
| 97356 | 4 | 2/0 - 14 | 3.13 | 1.75 | 1.38 | 6 |
| 97358 | 5 | 2/0 - 14 | 3.88 | 1.75 | 1.38 | 4 |
| 97360 | 6 | 2/0 - 14 | 4.63 | 1.75 | 1.38 | 4 |
| 97362 | 8 | 2/0 - 14 | 6.13 | 1.75 | 1.38 | 3 |
| 97392 | 2 | 250MCM - 6 | 2.13 | 2.63 | 2.13 | 6 |
| 97394 | 3 | 250MCM - 6 | 3.13 | 2.63 | 2.13 | 6 |
| 97396 | 4 | 250MCM - 6 | 4.13 | 2.63 | 2.13 | 6 |
| 97398 | 5 | 250MCM - 6 | 5 | 2.63 | 2.13 | 4 |
| 97400 | 6 | 250MCM - 6 | 6 | 2.63 | 2.13 | 4 |
| 97402 | 8 | 250MCM - 6 | 8 | 2.63 | 2.13 | 3 |
| 97412 | 2 | 350MCM - 10 | 2.25 | 3.13 | 2.5 | 3 |
| 97414 | 3 | 350MCM - 10 | 3.25 | 3.13 | 2.5 | 3 |
| 97416 | 4 | 350MCM - 10 | 4.25 | 3.13 | 2.5 | 3 |
| 97418 | 5 | 350MCM - 10 | 5.25 | 3.13 | 2.5 | 3 |
| 97420 | 6 | 350MCM - 10 | 6.25 | 3.13 | 2.5 | 2 |
| 97422 | 8 | 350MCM - 10 | 8.25 | 3.13 | 2.5 | 2 |
| 97432 | 2 | 500MCM - 6 | 2.88 | 3.38 | 2.75 | 3 |
| 97434 | 3 | 500MCM - 6 | 4.13 | 3.38 | 2.75 | 3 |
| 97436 | 4 | 500MCM - 6 | 5.38 | 3.38 | 2.75 | 3 |
| 97438 | 5 | 500MCM - 6 | 6.63 | 3.38 | 2.75 | 2 |
| 97440 | 6 | 500MCM - 6 | 7.88 | 3.38 | 2.75 | 2 |
| 97442 | 8 | 500MCM - 6 | 10.38 | 3.38 | 2.75 | 2 |