




# Rigid Steel Compression Box Connector



- Connect Thread-less Rigid Conduit to boxes and enclosures
- Zinc Plated Steel
- Concrete Tight
- Male Hub Thread (NPT)

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
I4360	1/2"	1.37	0.50	1.22	20	200
I4361	3/4"	1.44	0.53	1.46	10	100
I4362	1"	1.72	0.67	1.72	5	50
I4363	1-1/4"	1.93	0.68	2.15	5	50
I4364	1-1/2"	2.03	0.72	2.36	-	12
I4365	2"	2.02	0.72	2.89	-	12



Rigid Compression




# Rigid Steel Compression Insulated Box Connector

- Connect Thread-less Rigid Conduit to boxes and enclosures
- Zinc Plated Steel
- Insulated Throat
- Concrete Tight
- Male Hub Thread (NPT)

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
I4370	1/2"	1.37	0.51	1.22	20	200
I4371	3/4"	1.44	0.53	1.46	10	100
I4372	1"	1.72	0.67	1.72	5	50
I4373	1-1/4"	1.93	0.68	2.15	5	50
I4374	1-1/2"	2.03	0.72	2.36	-	12
I4375	2"	2.02	0.72	2.89	-	12



# Rigid Steel Compression Couplings

- Couple Sections of Thread-less Rigid Conduit together
- Zinc Plated Steel
- Concrete Tight

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
I4380	1/2"	1.83	1.22	10	100
I4381	3/4"	1.97	1.46	10	100
I4382	1"	2.11	1.72	5	50
I4383	1-1/4"	2.39	2.15	5	50
I4384	1-1/2"	2.52	2.36	-	12
I4385	2"	2.40	2.89	-	5

